

## Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: 409 00 01300-AN305-73 50 ml  
409 00 01310-AN305-735 75g  
Product name: MEDIUM THREADLOCKER

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Anaerobic product for thread braking

#### 1.3. Details of the supplier of the safety data sheet

Name: Meccanocar Italia S.r.l.  
Full address: Via San Francesco, 22  
District and Country: 56033 Capannoli (PI)  
Italy

Tel. +39 0587 609433

Fax +39 0587 607145

e-mail address of the competent person  
responsible for the Safety Data Sheet

moreno.meini@meccanocar.it

#### 1.4. Emergency telephone number

For urgent inquiries refer to

National Poisons Information Service: +44 121 507 4123

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Eye irritation, category 2  
Skin sensitization, category 1

H319  
H317

Causes serious eye irritation.  
May cause an allergic skin reaction.

#### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

## MEDIUM THREADLOCKER



Signal words: Warning

## Hazard statements:

**H319** Causes serious eye irritation.  
**H317** May cause an allergic skin reaction.

## Precautionary statements:

**P280** Wear protective gloves / eye protection / face protection.  
**P261** Avoid breathing dust / fume / gas / mist / vapours / spray.  
**P333+P313** If skin irritation or rash occurs: Get medical advice / attention.  
**P337+P313** If eye irritation persists: Get medical advice / attention.  
**P362+P364** Take off contaminated clothing and wash it before reuse.

**Contains:** 2-HYDROXYETHYL METHACRYLATE

## 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

## SECTION 3. Composition/information on ingredients

## 3.2. Mixtures

## Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
<b>2-HYDROXYETHYL METHACRYLATE</b> CAS 868-77-9 EC 212-782-2 INDEX - Reg. no. 01-2119490169-29-XXXX	$27 \leq x < 28,5$	Eye Irrit. 2 H319, Skin Sens. 1 H317, Classification note according to Annex VI to the CLP Regulation: D
<b>CUMENE HYDROPEROXIDE</b> CAS 80-15-9 EC 201-254-7 INDEX - Reg. no. 012119475796-19	$0,75 \leq x < 0,85$	Org. Perox E H242, Acute Tox. 3 H331, Acute Tox. 4 H302, Acute Tox. 4 H312, STOT RE 2 H373, Skin Corr. 1B H314, Eye Dam. 1 H318, Aquatic Chronic 2 H411

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## SECTION 4. First aid measures

**MEDIUM THREADLOCKER****4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

**4.3. Indication of any immediate medical attention and special treatment needed**

Information not available

**SECTION 5. Firefighting measures****5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

None in particular.

**5.2. Special hazards arising from the substance or mixture****HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Do not breathe combustion products.

**5.3. Advice for firefighters****GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**SECTION 6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

**6.2. Environmental precautions**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

## MEDIUM THREADLOCKER

**6.3. Methods and material for containment and cleaning up**

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage****7.1. Precautions for safe handling**

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

**7.2. Conditions for safe storage, including any incompatibilities**

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

**7.3. Specific end use(s)**

Information not available

**SECTION 8. Exposure controls/personal protection****8.1. Control parameters****2-HYDROXYETHYL METHACRYLATE**

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,482	mg/l
Normal value in marine water	0,482	mg/l
Normal value for fresh water sediment	3,79	mg/kg
Normal value for marine water sediment	3,79	mg/kg
Normal value of STP microorganisms	10	mg/l
Normal value for the terrestrial compartment	0,476	mg/kg

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers			Chronic systemic	Effects on workers			Chronic systemic
	Acute local	Acute systemic	Chronic local		Acute local	Acute systemic	Chronic local	
Oral				0,83 mg/kg bw/d				
Inhalation				2,9 mg/m3				4,9 mg/m3
Skin				0,83 mg/kg bw/d				1,3 mg/kg bw/d

**CUMENE HYDROPEROXIDE**

Predicted no-effect concentration - PNEC

## MEDIUM THREADLOCKER

Normal value in fresh water	0,003	mg/l
Normal value in marine water	0	mg/l
Normal value for fresh water sediment	0,023	mg/kg
Normal value for marine water sediment	0,002	mg/kg
Normal value of STP microorganisms	0,35	mg/l
Normal value for the terrestrial compartment	0,003	mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Effects on consumers				Effects on workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation								6 mg/m3

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

## 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

### SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

### 2-HYDROXYETHYL METHACRYLATE

Butyl rubber.

Breakthrough time: 480 min

## MEDIUM THREADLOCKER

Glove thickness: 0.3 mm

Guideline: EN 374

Additional Information: Observe the permeability and breakthrough time instructions provided by the glove supplier. Also take into consideration the specific local conditions in which the product is used, such as the danger of cuts, abrasions and contact times., The above mentioned hand protection is based on a specific knowledge of the chemical and of the expected handling of this product however, it may not be suitable for all workplaces. A qualified hazard assessment must be carried out before starting work in order to determine the suitability of the gloves for specific work environments and processes., The gloves must be discarded and replaced if there are indications of degradation or chemical innovation.

## CUMENE HYDROPEROXIDE

Respiratory equipment: use a respiratory filter with gas filter DIN EN 141 Type A (brown color code): up to 0.1 vol.% Class 1; up to 0.5 vol.% class 2; up to 1% by volume class 3; above 1% and if conditions are unclear, breathing device independent of the environment.

Hand protection: wear resistant protective gloves (tested according to DIN EN 374). Avoid direct contact with the chemical / product / preparation with organizational measures. The glove material must be impermeable and resistant to the product / the substance / the preparation. Check the protective gloves before each use for their proper conditions. After using gloves, apply skin cleaners and skin cosmetics. Selection of glove material in consideration of breakthrough times, diffusion rates and degradation

Glove material: fluorocarbon rubber, PVC

The choice of the ideal depends on the material and also on the quality of the gloves. The degree of protection varies from manufacturer to manufacturer. Since the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and must therefore be checked before application.

Eye protection: basketball glasses (DIN EN 58211, number 3), face protection.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	liquid
Colour	green
Odour	characteristic
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	> 100 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	Not available
Solubility	soluble in organic solvents
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	90-200000 cps
Explosive properties	Not available

Oxidising properties

Not available

#### 9.2. Other information

Information not available

## SECTION 10. Stability and reactivity

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 2-HYDROXYETHYL METHACRYLATE

Heat-evolving polymerization can occur in the presence of radical-forming substances (eg peroxides), reducing substances and / or heavy metal ions.

### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

#### 2-HYDROXYETHYL METHACRYLATE

Ultraviolet light. High temperature The product is normally supplied in a stabilized form. If the permitted storage period and / or storage temperature are exceeded, the product may polymerize with the evolution of heat.

#### CUMENE HYDROPEROXIDE

Temperatures above 80 ° C (decomposition of cumene hydroxide).

### 10.5. Incompatible materials

#### 2-HYDROXYETHYL METHACRYLATE

Peroxides, amines, sulfur compounds, heavy metal ions, alkalis, reducing agents and oxidizing agents.

#### CUMENE HYDROPEROXIDE

Risk of explosion in contact with rust, ash, dirt, accelerators such as salts of heavy metals and tertiary amines; vigorous reaction on contact with concentrated mineral acids and alkaline solutions and reducing agents!

## MEDIUM THREADLOCKER

**10.6. Hazardous decomposition products**

CUMENE HYDROPEROXIDE

Phenol, acetone.

**SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**11.1. Information on toxicological effects**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

&gt; 20 mg/l

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

Not classified (no significant component)

CUMENE HYDROPEROXIDE

LD50 (Oral) 382 mg/kg Rat

LD50 (Dermal) 0,126 mg/kg Rabbit

2-HYDROXYETHYL METHACRYLATE

Method: Chemical Safety Assessment by the Pharmacology Division Staff, FDA, 1959 in Food, Drugs and Cosmetics



## MEDIUM THREADLOCKER

Reliability: 2  
Species: Rat (Wistar)  
Route of exposure: Oral  
Results: LD50 = 5564 mg / kg bw  
Method: Not indicated  
Reliability: 2  
Species: Rabbit (male)  
Route of exposure: Dermal  
Results: LD50> 5000 mg / kg bw

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

## 2-HYDROXYETHYL METHACRYLATE

Method: Assessment of the safety of chemicals in food, drugs and cosmetics (1959)  
Reliability: 2  
Species: Rabbit (New Zealand White)  
Route of exposure: Dermal  
Results: Not classified

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

## 2-HYDROXYETHYL METHACRYLATE

Method: Evaluation of the safety of chemicals in food, drugs and cosmetics by the staff of the pharmacology division, FDA acc. to empty  
Reliability: 2  
Species: Rabbit (New Zealand White)  
Route of exposure: Ocular  
Results: Category 2B (slightly irritating to eyes)

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

Skin sensitization  
2-HYDROXYETHYL METHACRYLATE

Method: Not indicated  
Reliability: 2  
Species: guinea pig (Pirbright: male)  
Route of exposure: Dermal  
Results: Not sensitizing

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

## 2-HYDROXYETHYL METHACRYLATE

Method: OECD 471 in vitro test  
Reliability: 1  
Species: S. typhimurium, E. Coli  
Results: Negative with and without metabolic activation  
Method: OECD 474-test in vivo  
Reliability: 1

## MEDIUM THREADLOCKER

Species: Rat (Sprague-Dawley; male)  
Route of exposure: Oral  
Results: Negative

## CUMENE HYDROPEROXIDE

Method: Equivalent or similar to OECD 471 in vitro test  
Reliability: 2  
Species: S. typhimurium  
Results: Positive  
Method: Standard NTP-Test protocol in vivo  
Reliability: 1  
Species: Mouse (B6C3F1; male / female)  
Route of exposure: Dermal  
Results: Negative

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

## 2-HYDROXYETHYL METHACRYLATE

Method: Equivalent or similar to OECD 451  
Reliability: 1  
Species: Mouse (B6C3F1; male / female)  
Route of exposure: Inhalation  
Results: Negative

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

## CUMENE HYDROPEROXIDE

Adverse effects on sexual function and fertility  
2-HYDROXYETHYL METHACRYLATE

Method: OECD combined repeat reproduction toxicity and reproductive / developmental toxicity screening test (GL 422 precursor protocol)  
Reliability: 1  
Species: Rat (Crj: CD (SD); male / female)  
Route of exposure: Oral  
Results: NOAEL (fertility)> = 1000 mg / kg bw / day

## CUMENE HYDROPEROXIDE

Adverse effects on development of the offspring  
2-HYDROXYETHYL METHACRYLATE

Method: OECD 422  
Reliability: 1  
Species: Rat (Crj: CD (SD))  
Route of exposure: Oral  
Results: NOAEL (development)> = 1000 mg / kg bw / day

## CUMENE HYDROPEROXIDE

## MEDIUM THREADLOCKER

Method: OECD 414  
Reliability: 1  
Species: Rat (Wistar)  
Exposure route: oral  
Results: NOAEL (development) = 15 mg / kg bw / day

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

## 2-HYDROXYETHYL METHACRYLATE

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

## CUMENE HYDROPEROXIDE

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

## 2-HYDROXYETHYL METHACRYLATE

Method: OECD 422  
Reliability: 1  
Species: Rat (Crj: CD (SD); male / female)  
Route of exposure: Oral  
Results: NOAEL = 100 mg / kg bw / day  
Method: OECD 413  
Reliability: 1  
Species: Rat (Sprague-Dawley; male / female)  
Route of exposure: Inhalation  
Results: NOAEC = 100 ppm

## CUMENE HYDROPEROXIDE

Method: Not indicated  
Reliability: 2  
Species: Rat (Wistar; male)  
Route of exposure: Oral  
Results: Not classified  
Bibliographic reference: Toxicity studies of certain organic peroxides and hydroperoxides, Floyd EP, Stokinger HE, (1958)  
Method: Not indicated  
Reliability: 1  
Species: Rat (CDF; male / female)  
Route of exposure: Inhalation (aerosol)  
Results: NOAEC = 31 mg / m3 air

Target organ  
CUMENE HYDROPEROXIDE

Lung

Route of exposure  
CUMENE HYDROPEROXIDE

Inhalation

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

**SECTION 12. Ecological information**

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

**12.1. Toxicity****CUMENE HYDROPEROXIDE**

LC50 - for Fish	3,9 mg/l/96h
EC50 - for Crustacea	18,84 mg/l/48h
EC50 - for Algae / Aquatic Plants	3,1 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	1 mg/l

**2-HYDROXYETHYL METHACRYLATE**

LC50 - for Fish	100 mg/l/96h
EC50 - for Crustacea	380 mg/l/48h
EC50 - for Algae / Aquatic Plants	836 mg/l/72h
EC10 for Crustacea	24,1 mg/l/28d
Chronic NOEC for Crustacea	24,1 mg/l
Chronic NOEC for Algae / Aquatic Plants	400 mg/l

**12.2. Persistence and degradability****2-HYDROXYETHYL METHACRYLATE**

Easily degradable in water, 84% in 28 days.

**12.3. Bioaccumulative potential**

Information not available

**12.4. Mobility in soil**

Information not available

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**12.6. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations**

## MEDIUM THREADLOCKER

**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

**CONTAMINATED PACKAGING**

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**2-HYDROXYETHYL METHACRYLATE**

Dispose of waste and residues in accordance with the requirements of local authorities.

**Disposal methods:**

Waste is dangerous. It must be disposed of in accordance with the regulations after consulting the competent local authorities and the disposal company in a suitable and authorized facility. Strictly controlled conditions during the disposal or treatment of air, waste water and waste. Do not add waste water to a biological waste water treatment plant. Bring waste water containing AOX for professional disposal. The key number for the waste must be determined according to the European waste type list (decision on the EU waste type list 2000/532 / EC) in collaboration with the disposal company / producer / authority Official.

**CUMENE HYDROPEROXIDE**

Dispose of in an appropriate incineration plant observing local regulations (s. EWC, European catalog of waste materials), if a new treatment is not possible (after adequate dilution and in small portions).

**SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

**14.1. UN number**

Not applicable

**14.2. UN proper shipping name**

Not applicable

**14.3. Transport hazard class(es)**

Not applicable

**14.4. Packing group**

Not applicable

## MEDIUM THREADLOCKER

**14.5. Environmental hazards**

Not applicable

**14.6. Special precautions for user**

Not applicable

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

Information not relevant

**SECTION 15. Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

## MEDIUM THREADLOCKER

## 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

## SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Org. Perox E	Organic peroxide, category E
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Skin Corr. 1B	Skin corrosion, category 1B
Eye Irrit. 2	Eye irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H242	Heating may cause a fire.
H331	Toxic if inhaled.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

## LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit

**MEDIUM THREADLOCKER**

- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
  4. Regulation (EU) 2015/830 of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
  12. Regulation (EU) 2016/1179 (IX Atp. CLP)
  13. Regulation (EU) 2017/776 (X Atp. CLP)
  14. Regulation (EU) 2018/669 (XI Atp. CLP)
  15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
  16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - IFA GESTIS website
  - ECHA website
  - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

**Changes to previous review:**

The following sections were modified:

01 / 02 / 03 / 04 / 05 / 07 / 08 / 09 / 10 / 11 / 12 / 13 / 14 / 15 / 16.