

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 411 00 00870-1805
Product name: MULTISTOFF UNLOCKING FLUID

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Liquid degreasing release agent

1.3. Details of the supplier of the safety data sheet

Name: Meccanocar Italia S.r.l.
Full address: Via San Francesco, 22
District and Country: 56033 Capannoli (PI)
Italy
Tel. +39 0587 609433
Fax +39 0587 607145

e-mail address of the competent person
responsible for the Safety Data Sheet

moreno.meini@meccanocar.it

1.4. Emergency telephone number

For urgent inquiries refer to: National Poisons Information Service: +44 121 507 4123

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aspiration hazard, category 1

H304

May be fatal if swallowed and enters airways.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

MULTISTOFF UNLOCKING FLUID

Signal words: Danger

Hazard statements:

H304 May be fatal if swallowed and enters airways.
EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331 Do NOT induce vomiting.
P201 Obtain special instructions before use.
P280 Wear protective gloves/ protective clothing / eye protection / face protection.
P308+P313 IF exposed or concerned: Get medical advice / attention.
P301+P310 IF SWALLOWED: immediately call a POISON CENTER / doctor.

Contains: DISTILLATES (PETROLEUM), NAPHTHENIC, LIGHT FROM HYDROTREATING
 NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients**3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY CAS 64742-82-1 EC 265-185-4 INDEX 649-330-00-2	70 ≤ x < 74	Carc. 1B H350, Muta. 1B H340, STOT RE 1 H372, Asp. Tox. 1 H304, Classification note according to Annex VI to the CLP Regulation: P
DISTILLATES (PETROLEUM), NAPHTHENIC, LIGHT FROM HYDROTREATING CAS 64742-53-6 EC 265-156-6 INDEX 649-466-00-2 Reg. no. 01-2119480375-34-XXXX	27 ≤ x < 28,5	Carc. 1B H350

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

MULTISTOFF UNLOCKING FLUID**6.2. Environmental precautions**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection**8.1. Control parameters**

Regulatory References:

ESP España LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)

NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m ³	ppm	mg/m ³	ppm	
VLA	ESP	290	50	580	100	SKIN
VLA	ESP	290	50	580	100	SKIN

Health - Derived no-effect level - DNEL / DMEL

Effects on consumers

Effects on workers

MULTISTOFF UNLOCKING FLUID

Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation	640 mg/m3	1152 mg/m3	178,57 mg/m3		1066,67 mg/m3	1286,4 mg/m3	837,5 mg/m3	
DISTILLATES (PETROLEUM), NAPHTHENIC, LIGHT FROM HYDROTREATING								
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,74 mg/kg bw/d				
Inhalation			1,19 mg/m3	2,73	5,58		5,58 mg/m3	2,73 mg/m3
Skin				0,97				0,97 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

The product must be used inside a closed circuit, in a well-ventilated environment and with strong localised aspiration systems in place.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

MULTISTOFF UNLOCKING FLUID

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	liquid
Colour	colourless
Odour	characteristic
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	160 °C
Boiling range	245 °C
Flash point	43 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	<0,1 kPa
Vapour density	Not available
Relative density	0,75
Solubility	insoluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	> 200 °C
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

Information not available

SECTION 10. Stability and reactivity**10.1. Reactivity**

MULTISTOFF UNLOCKING FLUID

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information**11.1. Information on toxicological effects**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

Not classified (no significant component)

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

Not classified (no significant component)

NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY

MULTISTOFF UNLOCKING FLUID

LD50 (Oral) > 5000 mg/kg Rat

LD50 (Dermal) > 2000 mg/kg Rabbit

DISTILLATES (PETROLEUM), NAPHTHENIC, LIGHT FROM HYDROTREATING

LD50 (Oral) 5000 mg/kg rat

LD50 (Dermal) 2000 mg/kg rabbit

LC50 (Inhalation) 2,18 mg/l/4h rat

DISTILLATES (PETROLEUM), NAPHTHENIC, LIGHT FROM HYDROTREATING

Method: OECD 401

Reliability: 1

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Oral

Results: LD50:> 5 000 mg / kg bw

Method: Equivalent or similar to OECD 403

Reliability: 1

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Inhalation (aerosol)

Results: LC50: 2.18 mg / L air

Method: OECD 402

Reliability: 1

Species: Rabbit (New Zealand White; male / female)

Route of exposure: Dermal

Results: LD50:> 5 000 mg / kg bw

SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.

DISTILLATES (PETROLEUM), NAPHTHENIC, LIGHT FROM HYDROTREATING

Method: Not indicated

Reliability: 2

Species: Rabbit (New Zealand White)

Route of exposure: Dermal

Results: Not irritating

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

DISTILLATES (PETROLEUM), NAPHTHENIC, LIGHT FROM HYDROTREATING

Method: Equivalent or similar to OECD 405

Reliability: 1

Species: Species: Rabbit (New Zealand White)

Route of exposure: Ocular

Results: Not irritating

RESPIRATORY OR SKIN SENSITISATION

MULTISTOFF UNLOCKING FLUID

Does not meet the classification criteria for this hazard class

DISTILLATES (PETROLEUM), NAPHTHENIC, LIGHT FROM HYDROTREATING

Method: Equivalent or similar to OECD 406

Reliability: 1

Species: guinea pig (Hartley; male)

Route of exposure: Dermal

Results: Not sensitizing

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

DISTILLATES (PETROLEUM), NAPHTHENIC, LIGHT FROM HYDROTREATING

Method: Equivalent or similar to OECD 471 in vitro test

Reliability: 1

Species: *S. typhimurium*

Results: Positive with metabolic activation

Method: Equivalent or similar to OECD 474 in vivo test

Reliability: 1

Species: Mouse (CD-1; male / female)

Route of exposure: Oral

Results: Negative

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

DISTILLATES (PETROLEUM), NAPHTHENIC, LIGHT FROM HYDROTREATING

Method: OECD 421

Reliability: 1

Species: Rat (CD BR Sprague Dawley; male / female)

Route of exposure: Oral

Results: Negative

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

DISTILLATES (PETROLEUM), NAPHTHENIC, LIGHT FROM HYDROTREATING

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

DISTILLATES (PETROLEUM), NAPHTHENIC, LIGHT FROM HYDROTREATING

MULTISTOFF UNLOCKING FLUID

Method: Equivalent or similar to OECD 408

Reliability: 1

Species: Rat (Sprague-Dawley; male)

Route of exposure: Oral

Results: NOAEL = 125 mg / kg bw / day

Method: Equivalent or similar to OECD 412-Read across

Reliability: 2

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Inhalation

Results: NOAEC > 980 mg / m³ air

Method: OECD 410-Read across

Reliability: 1

Species: Rabbit (New Zealand White; male / female)

Route of exposure: Dermal

Results: NOAEL = 1000 mg / kg bw / day

ASPIRATION HAZARD

Toxic for aspiration

SECTION 12. Ecological information**12.1. Toxicity**

NAPHTHA (PETROL.)

HYDRODESULFURIZED HEAVY

LC50 - for Fish

8,2 mg/l/96h Pimephales promelas

EC50 - for Crustacea

4,5 mg/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants

3,1 mg/l/72h Pseudokirchnerella subcapitata

12.2. Persistence and degradability

NAPHTHA (PETROL.)

HYDRODESULFURIZED HEAVY

Rapidly degradable

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

NAPHTHA (PETROL.)

HYDRODESULFURIZED HEAVY

Partition coefficient: soil/water

1,78

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

MULTISTOFF UNLOCKING FLUID

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3

Contained substance

Point	28-29	NAPHTHA (PETROL.) HYDRODESULFURI ZED HEAVY
Point	28	DISTILLATES (PETROLEUM), NAPHTHENIC, LIGHT FROM HYDROTREATING Reg. no.: 01- 2119480375-34- XXXX

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

MULTISTOFF UNLOCKING FLUIDHealthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Carc. 1B	Carcinogenicity, category 1B
Muta. 1B	Germ cell mutagenicity, category 1B
STOT RE 1	Specific target organ toxicity - repeated exposure, category 1
Asp. Tox. 1	Aspiration hazard, category 1
H350	May cause cancer.
H340	May cause genetic defects.
H372	Causes damage to organs through prolonged or repeated exposure.
H304	May be fatal if swallowed and enters airways.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

MULTISTOFF UNLOCKING FLUID**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

02 / 03 / 04 / 08 / 09 / 11 / 12 / 15 / 16.