

# Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

## SECTION 1. Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Code: 411 00 01040-1872  
Product name: NO FROST SPRAY

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: De-icing spray for locks and windshield

### 1.3. Details of the supplier of the safety data sheet

Name: Meccanocar Italia S.r.l.  
Full address: Via San Francesco, 22  
District and Country: 56033 Capannoli (PI)  
Italy  
Tel. +39 0587 609433  
Fax +39 0587 607145

e-mail address of the competent person  
responsible for the Safety Data Sheet

moreno.meini@meccanocar.it

### 1.4. Emergency telephone number

For urgent inquiries refer to

National Poisons Information Service: +44 121 507 4123

## SECTION 2. Hazards identification

### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222 H229	Extremely flammable aerosol. Pressurised container: may burst if heated.
Eye irritation, category 2	H319	Causes serious eye irritation.

### 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

**NO FROST SPRAY**

Signal words:

Danger

Hazard statements:

**H222** Extremely flammable aerosol.  
**H229** Pressurised container: may burst if heated.  
**H319** Causes serious eye irritation.

Precautionary statements:

**P210** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
**P251** Do not pierce or burn, even after use.  
**P410+P412** Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.  
**P211** Do not spray on an open flame or other ignition source.  
**P280** Wear eye protection / face protection.

**2.3. Other hazards**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**SECTION 3. Composition/information on ingredients****3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
<b>ETHANOL</b>		
CAS 64-17-5	54 ≤ x < 58	Flam. Liq. 2 H225, Eye Irrit. 2 H319
EC 200-578-6		
INDEX 603-002-00-5		
Reg. no. 01-2119457610-43-XXXX		
<b>BUTANE</b>		
CAS 106-97-8	6 ≤ x < 7	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C U
EC 203-448-7		
INDEX 601-004-00-0		
Reg. no. 01-2119474691-32-XXXX		
<b>ETHANEDIOL</b>		
CAS 107-21-1	4 ≤ x < 4,5	Acute Tox. 4 H302, STOT RE 2 H373
EC 203-473-3		
INDEX 603-027-00-1		
Reg. no. 01-2119456816-28-XXXX		
<b>PROPAN-2-OL</b>		

**NO FROST SPRAY**

CAS 67-63-0                       $2 \leq x < 2,5$                       Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336  
EC 200-661-7  
INDEX 603-117-00-0  
Reg. no. 01-2119457558-25-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 6,00 %

## SECTION 4. First aid measures

### 4.1. Description of first aid measures

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

**SKIN:** Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

**INHALATION:** Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

**INGESTION:** Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## SECTION 5. Firefighting measures

### 5.1. Extinguishing media

#### SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

#### UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

### 5.2. Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

### 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained

open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

### 6.2. Environmental precautions

Do not disperse in the environment.

### 6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage

### 7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

### 7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

### 7.3. Specific end use(s)

Information not available

## SECTION 8. Exposure controls/personal protection

### 8.1. Control parameters

Regulatory References:

ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition, published 2018)
ITA	Italia	DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017
NOR	Norge	Fastsatt av Arbeids- og sosialdepartementet 21. august 2018 med hjemmel i lov 17. juni 2005 nr. 62 om arbeidsmiljø, arbeidstid, stillingsvern mv. (arbeidsmiljøloven) § 1-3, § 1-4 og § 4-5
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018

**NO FROST SPRAY**

EU OEL EU Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.  
 TLV-ACGIH ACGIH 2019

**ETHANOL****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
VLA	ESP			1910	1000			
VLEP	FRA	1900	1000	9500	5000			
WEL	GBR	1920	1000					
TLV	NOR	950	500					
TLV-ACGIH				1884	1000			
<b>Predicted no-effect concentration - PNEC</b>								
Normal value in fresh water				0,96	mg/l			
Normal value in marine water				0,79	mg/l			
Normal value for fresh water sediment				3,6	mg/kg			
Normal value for marine water sediment				2,9	mg/kg			
Normal value of STP microorganisms				580	mg/l			
Normal value for the food chain (secondary poisoning)				0,38	mg/kg			
Normal value for the terrestrial compartment				0,63	mg/kg			

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				87 mg/kg bw/d				
Inhalation				114 mg/m3				950 mg/m3
Skin				206 mg/kg bw/d				343 mg/kg bw/d

**BUTANE****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
VLA	ESP		1000			Gases		
VLEP	FRA	1900	800					
WEL	GBR	1450	600	1810	750			
TLV	NOR	600	250					
TLV-ACGIH						1000		

**ETHANEDIOL****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
VLA	ESP	52	20	104	40	SKIN		
VLEP	FRA	52	20	104	40	SKIN		
WEL	GBR	52	20	104	40	SKIN		

**NO FROST SPRAY**

VLEP	ITA	52	20	104	40	SKIN
TLV	NOR	52	20			SKIN
VLE	PRT	52	20	104	40	SKIN
OEL	EU	52	20	104	40	SKIN
TLV-ACGIH				10		INHAL
TLV-ACGIH			25		50	

Predicted no-effect concentration - PNEC						
Normal value in fresh water				10		mg/l
Normal value in marine water				1		mg/l
Normal value for fresh water sediment				37		mg/kg
Normal value for marine water sediment				3,7		mg/kg
Normal value of STP microorganisms				199,5		mg/l
Normal value for the terrestrial compartment				1,53		mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation			7 mg/m3				35 mg/m3	
Skin				53 mg/kg bw/d				106 mg/kg bw/d

**PROPAN-2-OL**  
**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	500	200	1000	400	
VLEP	FRA			980	400	
WEL	GBR	999	400	1250	500	
TLV	NOR	245	100			
TLV-ACGIH		492	200	983	400	

Predicted no-effect concentration - PNEC						
Normal value in fresh water				140,9		mg/l
Normal value in marine water				140,9		mg/l
Normal value for fresh water sediment				552		mg/kg
Normal value for marine water sediment				552		mg/kg
Normal value of STP microorganisms				2251		mg/l
Normal value for the food chain (secondary poisoning)				160		mg/kg
Normal value for the terrestrial compartment				28		mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				26 mg/kg bw/d				
Inhalation				89 mg/m3				500 mg/m3
Skin				319 mg/kg bw/d				888 mg/kg bw/d

**NO FROST SPRAY**

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

**8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

**HAND PROTECTION**

None required.

**SKIN PROTECTION**

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

**ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

**PROPAN-2-OL**

Respiratory protection: personal respiratory protection devices are normally not required. In inadequately ventilated areas, where workplace limits are exceeded, where there are unpleasant odors or where aerosols are present or smoke and fog occur, use a self-contained breathing apparatus or self-contained breathing apparatus with a type A filter or an appropriate combined filter, in compliance with EN 141.

Hand protection: the choice of an appropriate glove depends not only on its material but also on other quality characteristics and is different from one manufacturer to another. Observe the permeability and breakthrough time instructions provided by the glove supplier. Also take into consideration the specific local conditions in which the product is used, such as the danger of cuts, abrasions and contact times. Keep in mind that in daily use the durability of a chemical resistant protective glove can be considerably less than breakthrough time measured according to EN 374.

**SECTION 9. Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Appearance	aerosol
Colour	colourless
Odour	characteristic
Odour threshold	Not available

## NO FROST SPRAY

pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	-26 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	Not available
Solubility	Not available
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

**9.2. Other information**

Information not available

**SECTION 10. Stability and reactivity****10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

**ETHANEDIOL**

In the air absorbs moisture. Decomposes at temperatures above 200°C/392°F.

**10.2. Chemical stability**

The product is stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions**

No hazardous reactions are foreseeable in normal conditions of use and storage.

**ETHANOL**

Risk of explosion on contact with: alkaline metals, alkaline oxides, calcium hypochlorite, sulphur monofluoride, acetic anhydride, acids, concentrated hydrogen peroxide, perchlorates, perchloric acid, perchloronitrile, mercury nitrate, nitric acid, silver, silver nitrate, ammonia, silver oxide, ammonia, strong oxidising agents, nitrogen dioxide. May react dangerously with: bromoacetylene, chlorine acetylene, bromine trifluoride, chromium trioxide, chromyl chloride, fluorine, potassium tert-butoxide, lithium hydride, phosphorus trioxide, black platinum, zirconium (IV) chloride, zirconium (IV) iodide. Forms explosive

**NO FROST SPRAY**

mixtures with: air.

**BUTANE**

Vapors can form an explosive mixture with air.

**ETHANEDIOL**

Risk of explosion on contact with: perchloric acid. May react dangerously with: chlorosulphuric acid, sodium hydroxide, sulphuric acid, phosphorus pentasulphide, chromium (III) oxide, chromyl chloride, potassium perchlorate, potassium dichromate, sodium peroxide, aluminium. Forms explosive mixtures with: air.

**PROPAN-2-OL**

Vapors can form an explosive mixture with air.

**10.4. Conditions to avoid**

Avoid overheating.

**ETHANOL**

Avoid exposure to: sources of heat, naked flames.

High temperature. Proximity to sources of ignition

**BUTANE**

Avoid heat and sources of ignition.

**ETHANEDIOL**

Avoid exposure to: sources of heat, naked flames.

**10.5. Incompatible materials**

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

**ETHANOL**

strong mineral acids, oxidizing agents. Aluminum at higher temperatures.

**BUTANE**

Strong oxidizing agents, chlorine, oxygen.

**10.6. Hazardous decomposition products**

## ETHANOL

Combustion will generate carbon oxides.

## BUTANE

In case of fire or production of thermal decomposition, for example, carbon monoxide, carbon dioxide (CO<sub>2</sub>).

## ETHANEDIOL

May develop: hydroxyacetaldehyde, glyoxal, acetaldehyde, methane, carbon monoxide, hydrogen.

**SECTION 11. Toxicological information****11.1. Information on toxicological effects**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

## ETHANEDIOL

WORKERS: inhalation; contact with the skin.

POPULATION: inhalation of ambient air; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

## ETHANEDIOL

Ingestion initially stimulates the central nervous system; later replaced by a phase of depression. There may be kidney damage, with anuria and uremia. Over-exposure symptoms are: vomiting, drowsiness, difficulty in breathing, convulsions. The lethal dose for humans is approx. 1.4 ml/kg.

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

Not classified (no significant component)

LD50 (Oral) of the mixture:

>2000 mg/kg

LD50 (Dermal) of the mixture:

Not classified (no significant component)

## PROPAN-2-OL

**NO FROST SPRAY**

LD50 (Oral) 4710 mg/kg Rat

LD50 (Dermal) 12800 mg/kg Rat

LC50 (Inhalation) 72,6 mg/l/4h Rat

**ETHANOL**

LD50 (Oral) > 5000 mg/kg Rat

LC50 (Inhalation) 120 mg/l/4h Pimephales promelas

**ETHANEDIOL**

LD50 (Oral) > 2000 mg/kg Rat

LD50 (Dermal) 9530 mg/kg Rabbit

**BUTANE**

Method: Not indicated

Reliability: 2

Species: Rat (Alderley Park (SPF); male / female)

Route of exposure: Inhalation

Results: LC50: 1 443 mg / L air

**PROPAN-2-OL**

Method: Equivalent or similar to OECD 401

Reliability: 2

Species: Rat (Sherman)

Route of exposure: Oral

Results: LD50: 5.84 other: g / kg body weight

Bibliographic reference: Smyth HF & Carpenter CP, FURTHER EXPERIENCE WITH THE RANGE FINDING TEST IN THE INDUSTRIAL TOXICOLOGY LABORATORY (1948)

Method: Equivalent or similar to OECD 403

Reliability: 1

Species: Rat (Fischer 344; male / female)

Route of exposure: Inhalation (vapor)

Results: LC50: ca. 5,000 ppm

Method: Equivalent or similar to OECD 402

Reliability: 2

Species: Rabbit

Route of exposure: Dermal

Results: LD50: 16.4 mL / kg bw

Bibliographic reference: Smyth HF & Carpenter CP, FURTHER EXPERIENCE WITH THE RANGE FINDING TEST IN THE INDUSTRIAL TOXICOLOGY LABORATORY (1948)

**SKIN CORROSION / IRRITATION**

Does not meet the classification criteria for this hazard class

**ETHANOL**

Method: OECD 404

**NO FROST SPRAY**

Reliability: 1  
Species: Rabbit (New Zealand White)  
Route of exposure: Dermal  
Results: Not irritating

**PROPAN-2-OL**

Method: Not indicated  
Reliability: 2  
Species: Rabbit  
Route of exposure: Dermal  
Results: Not classified  
Bibliographic reference: Nixon G, Tyson C & Wertz W, Interspecies Comparisons of Skin Irritancy (1975)

**SERIOUS EYE DAMAGE / IRRITATION**

Causes serious eye irritation

**PROPAN-2-OL**

Method: Equivalent or similar to OECD 405  
Reliability: 1  
Species: Rabbit (New Zealand White)  
Route of exposure: Ocular  
Results: Category 2

**RESPIRATORY OR SKIN SENSITISATION**

Does not meet the classification criteria for this hazard class

**PROPAN-2-OL**

Method: OECD 406  
Reliability: 1  
Species: guinea pig (Hartley; male / female)  
Route of exposure: Dermal  
Results: Not sensitizing

**GERM CELL MUTAGENICITY**

Does not meet the classification criteria for this hazard class

**ETHANOL**

Method: Equivalent or similar to OECD 478 in vivo test  
Reliability: 2  
Species: Mouse (CFLP and Alderley Park; male)  
Route of exposure: Oral  
Results: Negative

**BUTANE**

Method: OECD 471 in vitro test  
Reliability: 1  
Species: Salmonella strains, S. typhimurium  
Results: Negative without metabolic activation  
Method: OECD 474-test in vivo  
Reliability: 1  
Species: Rat (Sprague-Dawley CD; male / female)

**NO FROST SPRAY**

Route of exposure: Inhalation (gas)  
Results: Negative

**ETHANEDIOL**

Method: OECD 471 in vitro test

Reliability: 1

Species: *S. typhimurium*

Results: Negative with and without metabolic activation

Method: Assessing the possible effects of ethylene glycol for reproduction and dominant lethal mutagenesis.-test in vivo

Reliability: 2

Species: Rat (Fischer 344; male / female)

Route of exposure: Oral

Results: Negative

**PROPAN-2-OL**

Method: Equivalent or similar to OECD 476 in vitro test

Reliability: 1

Species: Chinese hamster

Results: Negative with or without metabolic activation

Bibliographic reference:

Method: Equivalent or similar to OECD 474 in vivo test

Reliability: 2

Species: Mouse (ICR; male / female)

Route of exposure: Oral

Results: Negative

**CARCINOGENICITY**

Does not meet the classification criteria for this hazard class

**ETHANEDIOL**

Available studies have shown no carcinogenic potential. In a carcinogenicity study lasting two years, carried out by the US National Toxicology Program (NTP), in which ethylene glycol was administered in the feed, "no evidence of carcinogenic activity" in male and female B6C3F1 mice was observed (NTP, 1993).

**REPRODUCTIVE TOXICITY**

Does not meet the classification criteria for this hazard class

**BUTANE**

Method: OECD 413

Reliability: 1

Species: Rat (Sprague-Dawley CD; male / female)

Route of exposure: Inhalation

Results: NOAEC 10000 ppm

**PROPAN-2-OL**

Method: Equivalent or similar to OECD 416

Reliability: 1

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Oral

Results: NOAEL 500

Adverse effects on development of the offspring

**ETHANOL**

**NO FROST SPRAY**

Method: Not indicated

Reliability: 2

Species: Rat (Sprague-Dawley)

Route of exposure: Oral

Results: NOAEL (development) 5.2 g ethanol / kg bw / day

Bibliographic reference: Prenatal ethanol exposure has differential effects on fetal growth and skeletal ossification, Simpson ME, Duggal S, & Keiver K (2005)

**STOT - SINGLE EXPOSURE**

Does not meet the classification criteria for this hazard class

**ETHANOL**

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

**BUTANE**

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

**ETHANEDIOL**

Based on available data and through expert judgment, the substance is classified in the target organ toxicity class for single exposure.

**PROPAN-2-OL**

Based on the available data, the substance may cause damage to organs through single exposure and is therefore classified in this hazard class.

Target organ

ETHANEDIOL

Kidney

Route of exposure

ETHANEDIOL

Oral

**PROPAN-2-OL**

inhalation

**STOT - REPEATED EXPOSURE**

Does not meet the classification criteria for this hazard class

**ETHANOL**

Method: Equivalent or similar to OECD 408

Reliability: 2

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Oral

Results: NOAEL 1 730 mg / kg bw / day

**BUTANE**

## NO FROST SPRAY

Method: OECD 413

Reliability: 1

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Inhalation (gas)

Results: NOAEC = 10000 ppm

## ETHANEDIOL

Method: OECD 410

Reliability: 1

Species: Dog (Beagle; male / female)

Route of exposure: Dermal

Results: NOAEL > 2 200 - < 4 400 mg / kg bw / day

## PROPAN-2-OL

Method: OECD 451

Reliability: 1

Species: Rat (Fischer 344; male / female)

Route of exposure: Inhalation (vapors)

Results: NOAEC = 5000 ppm

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

**SECTION 12. Ecological information****12.1. Toxicity**

Information not available

**12.2. Persistence and degradability**

## ETHANOL

Quickly biodegradable, 60% in 5 days.

## BUTANE

Quickly degradable in water.

## ETHANEDIOL

## PROPAN-2-OL

Quickly degradable in water.

## BUTANE

Solubility in water

0,1 - 100 mg/l

Rapidly degradable

## PROPAN-2-OL

Rapidly degradable

## ETHANOL

Solubility in water

1000 - 10000 mg/l

Rapidly degradable

**NO FROST SPRAY**

## ETHANEDIOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

**12.3. Bioaccumulative potential**

## BUTANE

Partition coefficient: n-octanol/water 1,09

## PROPAN-2-OL

Partition coefficient: n-octanol/water 0,05

## ETHANOL

Partition coefficient: n-octanol/water -0,35

## ETHANEDIOL

Partition coefficient: n-octanol/water -1,36

**12.4. Mobility in soil**

Information not available

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**12.6. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations****13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

**CONTAMINATED PACKAGING**

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**BUTANE**

No waste key number according to the European list of waste types can be assigned to this product, since this classification is based on the use (not yet determined) for which the product is intended for the consumer.

The key number for the waste must be determined according to the European waste type list (decision on the EU waste type list 2000/532 / EC) in collaboration with the disposal company / producer / authority Official.

**PROPAN-2-OL**

After pre-treatment and compliance with the regulations for hazardous waste, they must be taken to a permitted hazardous waste landfill or a hazardous waste incinerator.

## NO FROST SPRAY

## SECTION 14. Transport information

## 14.1. UN number

ADR / RID, IMDG, 1950  
IATA:

## 14.2. UN proper shipping name

ADR / RID: AEROSOLS  
IMDG: AEROSOLS  
IATA: AEROSOLS, FLAMMABLE

## 14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1

IMDG: Class: 2 Label: 2.1

IATA: Class: 2 Label: 2.1



## 14.4. Packing group

ADR / RID, IMDG, -  
IATA:

## 14.5. Environmental hazards

ADR / RID: NO  
IMDG: NO  
IATA: NO

## 14.6. Special precautions for user

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (D)
	Special Provision: -		
IMDG:	EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 150 Kg	Packaging instructions: 203
	Pass.:	Maximum quantity: 75 Kg	Packaging instructions: 203
	Special Instructions:	A145, A167, A802	

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

Information not relevant

**SECTION 15. Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

**15.2. Chemical safety assessment**

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

**Flam. Gas 1A** Flammable gas, category 1A

**NO FROST SPRAY**

<b>Aerosol 1</b>	Aerosol, category 1
<b>Aerosol 3</b>	Aerosol, category 3
<b>Flam. Liq. 2</b>	Flammable liquid, category 2
<b>Press. Gas (Liq.)</b>	Liquefied gas
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>STOT RE 2</b>	Specific target organ toxicity - repeated exposure, category 2
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>H220</b>	Extremely flammable gas.
<b>H222</b>	Extremely flammable aerosol.
<b>H229</b>	Pressurised container: may burst if heated.
<b>H225</b>	Highly flammable liquid and vapour.
<b>H280</b>	Contains gas under pressure; may burst if heated.
<b>H302</b>	Harmful if swallowed.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H319</b>	Causes serious eye irritation.
<b>H336</b>	May cause drowsiness or dizziness.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament

**NO FROST SPRAY**

7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
16. Regulation (EU) 2019/521 (XII Atp. CLP)

- The Merck Index. - 10th Edition

- Handling Chemical Safety

- INRS - Fiche Toxicologique (toxicological sheet)

- Patty - Industrial Hygiene and Toxicology

- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition

- IFA GESTIS website

- ECHA website

- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 04 / 08 / 09 / 10 / 11 / 12 / 13 / 14 / 15 / 16.