

## Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: 411 00 14830-2778  
Product name: CALCIUM GREASE

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Water repellent lubricating grease for boating

#### 1.3. Details of the supplier of the safety data sheet

Name: Meccanocar Italia S.r.l.  
Full address: Via San Francesco, 22  
District and Country: 56033 Capannoli (PI)  
Italy

Tel. +39 0587 609433

Fax +39 0587 607145

e-mail address of the competent person

responsible for the Safety Data Sheet: [moreno.meini@meccanocar.it](mailto:moreno.meini@meccanocar.it)

#### 1.4. Emergency telephone number

For urgent inquiries refer to: National Poisons Information Service: +44 121 507 4123

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2015/830.

Hazard classification and indication:

#### 2.2. Label elements

Hazard pictograms: --

Signal words: --

Hazard statements:

--

Precautionary statements:

## CALCIUM GREASE

--

**2.3. Other hazards**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**SECTION 3. Composition/information on ingredients****3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
<b>LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED</b>		
CAS 101316-72-7	$70 \leq x < 74$	Carc. 1A H350, Classification note according to Annex VI to the CLP Regulation: L
EC 309-877-7		
INDEX -		
Reg. no. 01-2119489969-06-XXXX		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

**SECTION 4. First aid measures****4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

**4.3. Indication of any immediate medical attention and special treatment needed**

Information not available

**SECTION 5. Firefighting measures****5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

**CALCIUM GREASE****UNSUITABLE EXTINGUISHING EQUIPMENT**

None in particular.

**5.2. Special hazards arising from the substance or mixture****HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Do not breathe combustion products.

**5.3. Advice for firefighters****GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**SECTION 6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

**6.2. Environmental precautions**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

**6.3. Methods and material for containment and cleaning up**

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage****7.1. Precautions for safe handling**

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

**7.2. Conditions for safe storage, including any incompatibilities**

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

**7.3. Specific end use(s)**

## CALCIUM GREASE

Information not available

## SECTION 8. Exposure controls/personal protection

### 8.1. Control parameters

#### LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED

Predicted no-effect concentration - PNEC

Normal value for the food chain (secondary poisoning)				9,33	mg/kg			
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,74 mg/kg bw/d				
Inhalation							5,58 mg/m3	2,73 mg/m3
Skin								0,97 mg/kg bw/d

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

The product must be used inside a closed circuit, in a well-ventilated environment and with strong localised aspiration systems in place.

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

#### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### ENVIRONMENTAL EXPOSURE CONTROLS

## CALCIUM GREASE

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	liquid
Colour	Not available
Odour	characteristic
Odour threshold	Not available
pH	Not available
Melting point / freezing point	> 160 °C
Initial boiling point	Not available
Boiling range	Not available
Flash point	> 200 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	Not available
Solubility	insoluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	> 300 °C
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	not explosive
Oxidising properties	non oxidizing

### 9.2. Other information

Information not available

## SECTION 10. Stability and reactivity

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

## CALCIUM GREASE

**10.3. Possibility of hazardous reactions**

No hazardous reactions are foreseeable in normal conditions of use and storage.

**10.4. Conditions to avoid**

None in particular. However the usual precautions used for chemical products should be respected.

**10.5. Incompatible materials**

Information not available

**10.6. Hazardous decomposition products**

Information not available

**SECTION 11. Toxicological information****11.1. Information on toxicological effects**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

Not classified (no significant component)

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

Not classified (no significant component)

LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED

Method: OECD 401-Read across

Reliability: 1

Species: Rat (Sprague-Dawley; male; female)

Route of exposure: Oral

Results: LD50> 5000 mg / kg bw

Method: Equivalent or similar to OECD 403-Read across

**CALCIUM GREASE**

Reliability: 1

Species: Rat (Sprague-Dawley; male; female)

Route of exposure: Inhalation (aerosol)

Results: LC50 = 2.18 mg / L air

Method: OECD 402-Read across

Reliability: 1

Species: Rabbit (New Zealand White; male / female)

Route of exposure: Dermal

Results: LD50> 5000 mg / kg bw

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED

Method: Not indicated

Reliability: 2

Species: Rabbit (New Zealand White)

Route of exposure: Dermal

Results: Not irritating

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED

Method: Equivalent or similar to OECD 405-Read across

Reliability: 1

Species: Rabbit (New Zealand White)

Route of exposure: Ocular

Results: Not irritating

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED

Method: Equivalent or similar to OECD 406-Read across

Reliability: 1

Species: guinea pig (Hartley; male)

Route of exposure: Dermal

Results: Not sensitizing

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED

Method: Equivalent or similar to OECD 471-Read across-test in vitro

Reliability: 1

Species: S. typhimurium

Results: Positive with metabolic activation

Method: OECD 474-Read across-test in vivo

Reliability: 1

Species: Mouse (CD-1; male / female)

## CALCIUM GREASE

Route of exposure: Oral

Results: Negative

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED

Method: Equivalent or similar to OECD 451-Read across

Reliability: 1

Species: Mouse (CF1; female)

Route of exposure: Dermal

Results: Negative

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

Adverse effects on sexual function and fertility

LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED

Method: OECD 421-Read across

Reliability: 1

Species: Rat (Sprague-Dawley; male; female)

Route of exposure: Oral

Results: Negative, NOAEL (fertility) > = 1000 mg / kg bw / day

Adverse effects on development of the offspring

LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED

Method: Equivalent or similar to OECD 414-Read across

Reliability: 1

Species: Rat (Sprague-Dawley)

Route of exposure: Dermal

Results: Positive, NOAEL (development) = 30 mg / kg bw / day

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED

Method: Equivalent or similar to OECD 408

Reliability: 1

Species: Rat (Sprague-Dawley; male)

Route of exposure: Oral

Results: Negative, NOAEL = 125 mg / kg bw

Method: Equivalent or similar to OECD 412-Read across

Reliability: 2



## CALCIUM GREASE

Species: Rat (Sprague-Dawley; male; female)

Route of exposure: Inhalation

Results: Negative, NOAEL = 200 mg / m<sup>3</sup>

Method: OECD 410-Read across

Reliability:

Species: Rabbit (New Zealand White; male / female)

Route of exposure: Dermal

Results: NOEL = 1000 mg / kg

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

**SECTION 12. Ecological information****12.1. Toxicity**

Information not available

**12.2. Persistence and degradability**

LUBRICANT OILS (PETROLEUM), C24-50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED

Not easily degradable in water, from 2 to 4% in 28 days.

**12.3. Bioaccumulative potential**

Information not available

**12.4. Mobility in soil**

Information not available

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**12.6. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations****13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**SECTION 14. Transport information**

## CALCIUM GREASE

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

**14.1. UN number**

Not applicable

**14.2. UN proper shipping name**

Not applicable

**14.3. Transport hazard class(es)**

Not applicable

**14.4. Packing group**

Not applicable

**14.5. Environmental hazards**

Not applicable

**14.6. Special precautions for user**

Not applicable

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

Information not relevant

**SECTION 15. Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: None

## CALCIUM GREASE

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Contained substance

Point	28	LUBRICANT OILS (PETROLEUM), C24- 50, EXTRACTS WITH SOLVENT, WAXED, HYDROGENATED Reg. no.: 01- 2119489969-06- XXXX
-------	----	---

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

## 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

## SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Carc. 1A</b>	Carcinogenicity, category 1A
<b>H350</b>	May cause cancer.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)

**CALCIUM GREASE**

- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
  4. Regulation (EU) 2015/830 of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
  12. Regulation (EU) 2016/1179 (IX Atp. CLP)
  13. Regulation (EU) 2017/776 (X Atp. CLP)
  14. Regulation (EU) 2018/669 (XI Atp. CLP)
  15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
  16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - IFA GESTIS website
  - ECHA website
  - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

**Changes to previous review:**

The following sections were modified:

01 / 02 / 03 / 04 / 06 / 07 / 08 / 09 / 11 / 12 / 13 / 14 / 15 / 16.