

## Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

**1.1. Product identifier**

Code:

**411 00 15235-2875**

Product name

**WATER BASED WELDING SPRAY****1.2. Relevant identified uses of the substance or mixture and uses advised against**

Intended use

**Anti-adhesive for aerosol welding sprays****1.3. Details of the supplier of the safety data sheet**

Name

**Meccanocar Italia S.r.l.**

Full address

**Via San Francesco, 22**

District and Country

**56033 Capannoli (PI)****Italy****Tel. +39 0587 609433****Fax +39 0587 607145**

e-mail address of the competent person

responsible for the Safety Data Sheet

**moreno.meini@meccanocar.it****1.4. Emergency telephone number**

For urgent inquiries refer to

**National Poisons Information Service: +44 121 507 4123**

### SECTION 2. Hazards identification

**2.1. Classification of the substance or mixture**

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1

**H222****Extremely flammable aerosol.****H229****Pressurised container: may burst if heated.****2.2. Label elements**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

## WATER BASED WELDING SPRAY



Signal words: Danger

## Hazard statements:

**H222** Extremely flammable aerosol.  
**H229** Pressurised container: may burst if heated.

## Precautionary statements:

**P210** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
**P251** Do not pierce or burn, even after use.  
**P410+P412** Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.  
**P211** Do not spray on an open flame or other ignition source.

## 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**SECTION 3. Composition/information on ingredients****3.2. Mixtures**

## Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
<b>METHYL OXIDE DIMETHYLETER</b>		
CAS 115-10-6	$10 \leq x < 25$	Flam. Gas 1A H220, Press. Gas H280
EC 204-065-8		
INDEX -		
Reg. no. 01-2119472128-37-XXXX		
<b>SODIUM NITRITE</b>		
CAS 7632-00-0	$0 \leq x < 2,5$	Ox. Sol. 2 H272, Acute Tox. 3 H301, Eye Irrit. 2 H319, Aquatic Acute 1 H400 M=1
EC 231-555-9		
INDEX 007-010-00-4		
Reg. no. 01-2119471836-27-XXXX		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 24,00 %

**WATER BASED WELDING SPRAY****SECTION 4. First aid measures****4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

**4.3. Indication of any immediate medical attention and special treatment needed**

Information not available

**SECTION 5. Firefighting measures****5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

None in particular.

**5.2. Special hazards arising from the substance or mixture****HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

**5.3. Advice for firefighters****GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**SECTION 6. Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

**6.2. Environmental precautions**

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

ITA                      Italia                      DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017

METHYL OXIDE DIMETHYLETER								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
VLEP	ITA	983	400			INHAL		
Predicted no-effect concentration - PNEC								
Normal value in fresh water				1,55		mg/l		
Normal value in marine water				0,16		mg/l		
Normal value for fresh water sediment				6,581		mg/kg		
Normal value for marine water sediment				0,69		mg/kg		
Normal value for water, intermittent release				1,549		mg/l		
Normal value for the terrestrial compartment				0,45		mg/kg		
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic

<b>Meccanocar Italia S.r.l.</b>	Revision nr. 2 Dated 12/02/2020
<b>WATER BASED WELDING SPRAY</b>	Printed on 12/02/2020 Page n. 5/15 Replaced revision:1 (Dated: 13/12/2019)

Inhalation 471 mg/m3 NPI 1894 mg/m3

#### SODIUM NITRITE

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,005	mg/l
Normal value in marine water	0,006	mg/l
Normal value for fresh water sediment	0,019	mg/kg
Normal value for marine water sediment	0,022	mg/kg
Normal value of STP microorganisms	21	mg/l
Normal value for the terrestrial compartment	0,001	mg/kg

#### Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation						2 mg/m3		2 mg/m3

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

**HAND PROTECTION**  
None required.

**SKIN PROTECTION**  
Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**  
Wear airtight protective goggles (see standard EN 166).

**RESPIRATORY PROTECTION**  
If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).  
Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

#### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

#### SODIUM NITRITE

Chemical resistant protective gloves (EN 374)  
Suitable materials also with prolonged direct contact (Recommended: protection index 6, corresponding to > 480 minutes of permeation time according to

## WATER BASED WELDING SPRAY

EN 374):  
polyvinyl chloride (PVC) - coating thickness 0.7 mm  
nitrile rubber (NBR) - coating thickness of 0.4 mm  
chloroprene rubber (CR) - coating thickness 0.5 mm  
Additional note: specifications are based on tests, literature data and information from glove manufacturers or derive from similar substances by analogy.  
Due to many conditions (eg temperature), it should be considered that the practical use of a chemical protective glove in practice can be much shorter than the breakthrough time determined through testing.  
The manufacturer's instructions for use must be observed due to the wide variety of types.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	aerosol
Colour	colourless
Odour	characteristic of solvent
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	< 0 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	0,9
Solubility	soluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

### 9.2. Other information

VOC (Directive 2010/75/EC) : 20,00 % - 180,00 g/litre

## SECTION 10. Stability and reactivity

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

## WATER BASED WELDING SPRAY

**10.2. Chemical stability**

The product is stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions**

No hazardous reactions are foreseeable in normal conditions of use and storage.

METHYL OXIDE DIMETHYLETER

Vapors can form an explosive mixture with air.

SODIUM NITRITE

Dangerous reactions in the presence of the mentioned substances to be avoided.

**10.4. Conditions to avoid**

Avoid overheating.

METHYL OXIDE DIMETHYLETER

Temperatures:> 52 ° C

SODIUM NITRITE

Reducing agents, oxidizable substances, ammonium salts, amines, amino compounds, acids

**10.5. Incompatible materials**

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

METHYL OXIDE DIMETHYLETER

Oxygen, oxidizing agents, acid anhydrides, strong acids, carbon monoxide, acetic anhydride, powdered metals.

**10.6. Hazardous decomposition products**

METHYL OXIDE DIMETHYLETER

Formaldehyde, carbon dioxide (CO<sub>2</sub>), carbon monoxide, methanol.

SODIUM NITRITE

Thermal decomposition:> 320 ° C  
nitrogen monoxide, nitrogen dioxide, disodium oxide

## WATER BASED WELDING SPRAY

**SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**11.1. Information on toxicological effects**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

Not classified (no significant component)

LD50 (Oral) of the mixture:

>2000 mg/kg

LD50 (Dermal) of the mixture:

Not classified (no significant component)

SODIUM NITRITE

LD50 (Oral) 180 mg/kg Rat

METHYL OXIDE DIMETHYLETER

LC50 (Inhalation) 164000 ppm/4h rat

METHYL OXIDE DIMETHYLETER

Method: Not indicated

Reliability: 2

Species: Rat (albino ChR-CD; male)

Route of exposure: Inhalation (gas)

Results: LC50: 164 000 ppm

SKIN CORROSION / IRRITATION



**WATER BASED WELDING SPRAY**

Does not meet the classification criteria for this hazard class

**SERIOUS EYE DAMAGE / IRRITATION**

Does not meet the classification criteria for this hazard class

**RESPIRATORY OR SKIN SENSITISATION**

Does not meet the classification criteria for this hazard class

**GERM CELL MUTAGENICITY**

Does not meet the classification criteria for this hazard class

**METHYL OXIDE DIMETHYLETER**

Method: OECD 471 in vitro test

Reliability: 1

Species: S. typhimurium

Results: Negative

Method: Equivalent or similar to OECD 477 in vivo test

Reliability: 2

Species: Drosophila melanogaster (male)

Route of exposure: Inhalation (gas)

Results: Negative

**CARCINOGENICITY**

Does not meet the classification criteria for this hazard class

**METHYL OXIDE DIMETHYLETER**

Method: Equivalent or similar to OECD 453

Reliability: 1

Species: Rat (CD (R) (SD) BR; male / female)

Route of exposure: Inhalation (vapors)

Results: Negative

**REPRODUCTIVE TOXICITY**

Does not meet the classification criteria for this hazard class

**METHYL OXIDE DIMETHYLETER**

Method: Equivalent or similar to OECD 452

Reliability: 1

Species: Rat (CD (SD) BR; male / female)

Route of exposure: Inhalation (vapors)

Results: Negative

**STOT - SINGLE EXPOSURE**

Does not meet the classification criteria for this hazard class

**METHYL OXIDE DIMETHYLETER**

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

## WATER BASED WELDING SPRAY

## SODIUM NITRITE

Based on available data and through expert judgment, the substance is not classified in the target organ hazard class for single exposure.

## STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

## METHYL OXIDE DIMETHYLETER

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for prolonged or repeated exposure.

## SODIUM NITRITE

Based on available data and through expert judgment, the substance is not classified in the target organ hazard class for prolonged or repeated exposure.

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

**SECTION 12. Ecological information**

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

**12.1. Toxicity**

## SODIUM NITRITE

LC50 - for Fish	0,79 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	23,31 mg/l/48h Penaeus monodon
EC50 - for Algae / Aquatic Plants	159 mg/l/72h Tetraseimis chui

## METHYL OXIDE DIMETHYLETER

LC50 - for Fish	4100 mg/l/96h
EC50 - for Crustacea	4400 mg/l/48h
EC50 - for Algae / Aquatic Plants	154,917 mg/l/72h
Chronic NOEC for Fish	4100 mg/l
Chronic NOEC for Crustacea	4400 mg/l

**12.2. Persistence and degradability**

## SODIUM NITRITE

Solubility in water	848000 mg/l
Degradability: information not available	

## WATER BASED WELDING SPRAY

## METHYL OXIDE DIMETHYLETER

Solubility in water 45600 mg/l

**12.3. Bioaccumulative potential**

## SODIUM NITRITE

Partition coefficient: n-octanol/water -3,7

## METHYL OXIDE DIMETHYLETER

Partition coefficient: n-octanol/water 0,07 Log Kow

**12.4. Mobility in soil**

Information not available

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**12.6. Other adverse effects**

Information not available

**SECTION 13. Disposal considerations****13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

**CONTAMINATED PACKAGING**

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## METHYL OXIDE DIMETHYLETER

It can be used after reconditioning. In accordance with local and national regulations. It must be incinerated in a suitable incineration plant in possession of an authorization issued by the competent authorities.

**SECTION 14. Transport information****14.1. UN number**

ADR / RID, IMDG, 1950  
IATA:

**14.2. UN proper shipping name**

ADR / RID: AEROSOLS  
IMDG: AEROSOLS

## WATER BASED WELDING SPRAY

IATA: AEROSOLS, FLAMMABLE

## 14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1

IMDG: Class: 2 Label: 2.1

IATA: Class: 2 Label: 2.1



## 14.4. Packing group

ADR / RID, IMDG, -  
IATA:

## 14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

## 14.6. Special precautions for user

ADR / RID: HIN - Kemler: --

Limited  
Quantities: 1  
LTunnel  
restriction  
code: (D)IMDG: Special Provision: -  
EMS: F-D, S-ULimited  
Quantities: 1  
L

IATA: Cargo:

Maximum  
quantity: 150  
Kg  
Maximum  
quantity: 75  
Kg  
A145, A167,  
A802Packaging  
instructions:  
203  
Packaging  
instructions:  
203

Pass.:

Special Instructions:

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

## SECTION 15. Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

## WATER BASED WELDING SPRAY

Product

Point 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

**15.2. Chemical safety assessment**

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Gas 1A</b>	Flammable gas, category 1A
<b>Aerosol 1</b>	Aerosol, category 1
<b>Aerosol 3</b>	Aerosol, category 3
<b>Ox. Sol. 2</b>	Oxidising solid, category 2
<b>Press. Gas</b>	Pressurised gas
<b>Acute Tox. 3</b>	Acute toxicity, category 3
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Aquatic Acute 1</b>	Hazardous to the aquatic environment, acute toxicity, category 1
<b>H220</b>	Extremely flammable gas.
<b>H222</b>	Extremely flammable aerosol.
<b>H229</b>	Pressurised container: may burst if heated.
<b>H272</b>	May intensify fire; oxidiser.
<b>H280</b>	Contains gas under pressure; may burst if heated.
<b>H301</b>	Toxic if swallowed.

## WATER BASED WELDING SPRAY

**H319** Causes serious eye irritation.

**H400** Very toxic to aquatic life.

## LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

## GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
  4. Regulation (EU) 2015/830 of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
  12. Regulation (EU) 2016/1179 (IX Atp. CLP)
  13. Regulation (EU) 2017/776 (X Atp. CLP)
  14. Regulation (EU) 2018/669 (XI Atp. CLP)
  15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
  16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - IFA GESTIS website
  - ECHA website
  - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

## Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety

**WATER BASED WELDING SPRAY**

laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

02 / 03 / 08 / 09 / 10 / 11 / 12 / 13 / 15 / 16.