

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 411 00 15330-2940
Product name: SANITIZER FOR HELMETS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Sanitizing detergent for the interiors of car / motorcycle helmets

1.3. Details of the supplier of the safety data sheet

Name: Meccanocar Italia S.r.l.
Full address: Via San Francesco, 22
District and Country: 56033 Capannoli (PI)
Italy
Tel. +39 0587 609433
Fax +39 0587 607145

e-mail address of the competent person
responsible for the Safety Data Sheet

moreno.meini@meccanocar.it

1.4. Emergency telephone number

For urgent inquiries refer to

National Poisons Information Service: +44 121 507 4123

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Aerosol, category 1	H222 H229	Extremely flammable aerosol. Pressurised container: may burst if heated.
Serious eye damage, category 1	H318	Causes serious eye damage.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

SANITIZER FOR HELMETS



Signal words: Danger

Hazard statements:

H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
P211 Do not spray on an open flame or other ignition source.
P260 Do not breathe dust / fume / gas / mist / vapours / spray.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Contains: BENZALKONIUM CHLORIDE
 SODIUM N-LAUROILSARCOSINATE
 SODIUM NITRITE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
BUTANE		
CAS 106-97-8	24 ≤ x < 25,5	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: C U
EC 203-448-7		
INDEX 601-004-00-0		
Reg. no. 01-2119474691-32-XXXX		
PROPANE		
CAS 74-98-6	24 ≤ x < 25,5	Flam. Gas 1A H220, Press. Gas (Liq.) H280, Classification note according to Annex VI to the CLP Regulation: U
EC 200-827-9		
INDEX 601-003-00-5		
Reg. no. 01-2119486944-21-XXXX		
ISOBUTANE		

SANITIZER FOR HELMETS

CAS 75-28-5 $24 \leq x < 25,5$ Flam. Gas 1A H220, Press. Gas H280

EC 200-857-2

INDEX 601-004-00-0

Reg. no. 01-2119485395-27-XXXX

SODIUM NITRITE

CAS 7632-00-0 $2 \leq x < 2,5$ Ox. Sol. 2 H272, Acute Tox. 3 H301, Eye Irrit. 2 H319, Aquatic Acute 1 H400 M=1

EC 231-555-9

INDEX 007-010-00-4

Reg. no. 01-2119471836-27-XXXX

BENZALKONIUM CHLORIDE

CAS 63449-41-2 $2 \leq x < 2,5$ Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Corr. 1B H314, Eye Dam. 1 H318, Aquatic Acute 1 H400 M=1

EC 264-151-6

INDEX 612-140-00-5

SODIUM N-LAUROILSARCOSINATE

CAS 137-16-6 $2 \leq x < 2,5$ Acute Tox. 1 H330, Eye Dam. 1 H318, Skin Irrit. 2 H315

EC 205-281-5

INDEX -

Reg. no. 01-2119527780-39-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

The product is an aerosol containing propellants. For the purposes of calculation of the health hazards, propellants are not considered (unless they have health hazards). The percentages indicated are inclusive of the propellants.

Percentage of propellants: 72,00 %

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

SANITIZER FOR HELMETS**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

If overheated, aerosol cans can deform, explode and be propelled considerable distances. Put a protective helmet on before approaching the fire. Do not breathe combustion products.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site. Send away individuals who are not suitably equipped. Wear protective gloves / protective clothing / eye protection / face protection.

6.2. Environmental precautions

Do not disperse in the environment.

6.3. Methods and material for containment and cleaning up

Use inert absorbent material to soak up leaked product. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Avoid bunching of electrostatic charges. Do not spray on flames or incandescent bodies. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Do not eat, drink or smoke during use. Do not breathe spray.

7.2. Conditions for safe storage, including any incompatibilities

Store in a place where adequate ventilation is ensured, away from direct sunlight at a temperature below 50°C / 122°F, away from any combustion sources.

SANITIZER FOR HELMETS

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition,published 2018)
NOR	TLV-ACGIH	ACGIH 2019
	RCP TLV	ACGIH TLVs and BEIs – Appendix H

ISOBUTANE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
RCP TLV			1000			RESP

PROPANE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP		1000			
TLV	NOR	900	500			
TLV-ACGIH			1000			

BUTANE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP		1000			Gases
VLEP	FRA	1900	800			
WEL	GBR	1450	600	1810	750	
TLV	NOR	600	250			
TLV-ACGIH					1000	

SODIUM N-LAUROILSARCOSINATE

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,009	mg/l
Normal value in marine water	0,001	mg/l
Normal value for fresh water sediment	0,064	mg/kg
Normal value for marine water sediment	0,006	mg/kg
Normal value of STP microorganisms	3	mg/l

SANITIZER FOR HELMETS

Normal value for the terrestrial compartment 0,008 mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral						10 mg/kg bw/d		
Inhalation				17,39 mg/m3				70,53 mg/m3
Skin				10 mg/kg bw/d				20 mg/kg bw/d

SODIUM NITRITE

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,005	mg/l
Normal value in marine water	0,006	mg/l
Normal value for fresh water sediment	0,019	mg/kg
Normal value for marine water sediment	0,022	mg/kg
Normal value of STP microorganisms	21	mg/l
Normal value for the terrestrial compartment	0,001	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation						2 mg/m3		2 mg/m3

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

None required.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

SANITIZER FOR HELMETS**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, a mask with a type AX filter combined with a type P filter should be worn (see standard EN 14387).

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

ISOBUTANE

Suitable glove material protective gloves, e.g. nitrile butadiene rubber gloves (NBR), leather gloves, heat insulating

Selection of protective gloves to meet specific workplace requirements.

Suitability for specific workplaces must be clarified with the manufacturers of protective gloves.

The information is based on our tests, references from literature and information from glove manufacturers or derived by analogy with similar materials.

Remember that the useful time per day of a chemical protection glove can be much shorter than the breakthrough time determined according to EN 374 due to the numerous influencing factors involved.

SODIUM NITRITE

Chemical resistant protective gloves (EN 374)

Suitable materials also with prolonged direct contact (Recommended: protection index 6, corresponding to > 480 minutes of breakthrough time according to EN 374):

polyvinyl chloride (PVC) - coating thickness 0.7 mm

nitrile rubber (NBR) - coating thickness of 0.4 mm

chloroprene rubber (CR) - coating thickness 0.5 mm

Additional note: specifications are based on tests, literature data and information from glove manufacturers or derive from similar substances by analogy.

Due to many conditions (eg temperature), it should be considered that the practical use of a chemical protective glove in practice can be much shorter than the breakthrough time determined through testing.

The manufacturer's instructions for use must be observed due to the wide variety of types.

SECTION 9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Appearance	liquid
Colour	transparent
Odour	characteristic
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	< 0 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available

SANITIZER FOR HELMETS

Vapour pressure	Not available
Vapour density	Not available
Relative density	0,726
Solubility	soluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

VOC (Directive 2010/75/EC) : 50,06 % - 363,44 g/litre

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

BENZALKONIUM CHLORIDE

Corrodes: carbon steel,copper,aluminium,copper alloys,aluminium alloys.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

ISOBUTANE

Vapors can form an explosive mixture with air.

BUTANE

Vapors can form an explosive mixture with air.

SODIUM NITRITE

Dangerous reactions in the presence of the mentioned substances to be avoided.

10.4. Conditions to avoid

Avoid overheating.

ISOBUTANE

Keep away from heat and other causes of fire.

BUTANE

Avoid heat and sources of ignition.

SODIUM N-LAUROILSARCOSINATE

Strong oxidizing agents.

SODIUM NITRITE

Reducing agents, oxidizable substances, ammonium salts, amines, amino compounds, acids

10.5. Incompatible materials

Strong reducing or oxidising agents, strong acids or alkalis, hot material.

ISOBUTANE

Strong oxidizing agents, chlorine, oxygen.

BUTANE

Strong oxidizing agents, chlorine, oxygen.

10.6. Hazardous decomposition products

ISOBUTANE

In case of fire or production of thermal decomposition, for example, carbon monoxide, carbon dioxide (CO₂).

BUTANE

In case of fire or production of thermal decomposition, for example, carbon monoxide, carbon dioxide (CO₂).

SODIUM N-LAUROILSARCOSINATE

In case of fire, dangerous decomposition products can be formed such as; Carbon oxides, nitrogen oxides (NO_x).

SANITIZER FOR HELMETS

SODIUM NITRITE

Thermal decomposition: > 320 ° C
nitrogen monoxide, nitrogen dioxide, disodium oxide

SECTION 11. Toxicological information**11.1. Information on toxicological effects**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

0,07 mg/l

LD50 (Oral) of the mixture:

1166,67 mg/kg

LD50 (Dermal) of the mixture:

>2000 mg/kg

SODIUM N-LAUROILSARCOSINATE

LC50 (Inhalation) > 0,05 mg/l/4h Rat (Wistar; male/female)

PROPANE

Method: To study the concentrations at which the effects of the CNS occur following exposure by inhalation to propane by measuring LC50 (15 min) and EC50 (CNS) (10 min) in rats.

Reliability: 2

Species: Rat (Alderley Park (SPF); male / female)

Route of exposure: Inhalation

Results: LC50 > 800 000 ppm

BUTANE

Method: Not indicated

SANITIZER FOR HELMETS

Reliability: 2

Species: Rat (Alderley Park (SPF); male / female)

Route of exposure: Inhalation

Results: LC50: 1 443 mg / L air

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

SODIUM N-LAUROILSARCOSINATE

Method: OECD Guideline 405

Reliability: 1

Species: Rabbit (albino SPF - Littlerussian)

Route of exposure: Ocular

Results: Eye irritation 2, H319

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

PROPANE

Method: OECD 471 in vitro test

Reliability: 1

Species: Histidine Salmonella

Results: Negative with or without metabolic activation

Method: OECD 474-test in vivo

Reliability: 1

Species: Rat (Sprague-Dawley CD; male / female)

Route of exposure: Inhalation (gas)

Results: Negative

BUTANE

Method: OECD 471 in vitro test

Reliability: 1

Species: Salmonella strains, S. typhimurium

Results: Negative without metabolic activation

Method: OECD 474-test in vivo

Reliability: 1

Species: Rat (Sprague-Dawley CD; male / female)

Route of exposure: Inhalation (gas)

Results: Negative

SODIUM N-LAUROILSARCOSINATE

Method: Equivalent or similar to OECD Guideline 471 - in vitro test

Reliability: 2

Species: S. typhimurium

Results: Negative with and without metabolic activation

SANITIZER FOR HELMETSCARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

BUTANE

Method: OECD 413

Reliability: 1

Species: Rat (Sprague-Dawley CD; male / female)

Route of exposure: Inhalation

Results: NOAEC 10000 ppm

Adverse effects on sexual function and fertility

PROPANE

Method: OECD 413

Reliability: 1

Species: Rat (Sprague-Dawley CD; male / female)

Route of exposure: Inhalation

Results: NOAEC (fertility) 10 000 ppm

Adverse effects on development of the offspring

PROPANE

Method: EPA OPPTS 870.3700

Reliability: 1

Species: Rat (VAF / Plus®, Sprague-Dawley Derived (CD®) CrI: CD® IGS BR)

Route of exposure: Inhalation (gas)

Results: NOAEC (development) 10 426 ppm

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

ISOBUTANE

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

PROPANE

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

BUTANE

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

SODIUM N-LAUROILSARCOSINATE

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

SODIUM NITRITE

SANITIZER FOR HELMETS

Based on available data and through expert judgment, the substance is not classified in the target organ hazard class for single exposure.

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ISOBUTANE

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for prolonged or repeated exposure.

PROPANE

Method: OECD 422

Reliability: 1

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Inhalation (gas)

Results: NOAEC 16 000 ppm

BUTANE

Method: OECD 413

Reliability: 1

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Inhalation (gas)

Results: NOAEC = 10000 ppm

SODIUM N-LAUROILSARCOSINATE

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for prolonged or repeated exposure.

SODIUM NITRITE

Based on available data and through expert judgment, the substance is not classified in the target organ hazard class for prolonged or repeated exposure.

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information**12.1. Toxicity**

SODIUM NITRITE

LC50 - for Fish

0,79 mg/l/96h *Oncorhynchus mykiss*

EC50 - for Crustacea

23,31 mg/l/48h *Penaeus monodon*

EC50 - for Algae / Aquatic Plants

159 mg/l/72h *Tetrarseimis chui*

SODIUM N-LAUROILSARCOSINATE

SANITIZER FOR HELMETS

LC50 - for Fish	32,1 mg/l/96h
EC50 - for Crustacea	29,7 mg/l/48h
EC50 - for Algae / Aquatic Plants	79 mg/l/72h
EC10 for Algae / Aquatic Plants	9,2 mg/l/72h
Chronic NOEC for Algae / Aquatic Plants	9,2 mg/l

12.2. Persistence and degradability

BUTANE
Quickly degradable in water.

BUTANE	
Solubility in water	0,1 - 100 mg/l
Rapidly degradable	

SODIUM NITRITE	
Solubility in water	848000 mg/l
Degradability: information not available	

BENZALKONIUM CHLORIDE
NOT rapidly degradable

PROPANE	
Solubility in water	0,1 - 100 mg/l
Rapidly degradable	

12.3. Bioaccumulative potential

BUTANE	
Partition coefficient: n-octanol/water	1,09

SODIUM NITRITE	
Partition coefficient: n-octanol/water	-3,7

PROPANE	
Partition coefficient: n-octanol/water	1,09

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

ISOBUTANE

Compliance with local regulations, e.g. incineration through flaring system.

No waste key number according to the European list of waste types can be assigned to this product, since this classification is based on the use (not yet determined) for which the product is intended for the consumer.

The key number for the waste must be determined according to the European waste type list (decision on the EU waste type list 2000/532 / EC) in collaboration with the disposal company / producer / authority Official.

BUTANE

No waste key number according to the European list of waste types can be assigned to this product, since this classification is based on the use (not yet determined) for which the product is intended for the consumer.

The key number for the waste must be determined according to the European waste type list (decision on the EU waste type list 2000/532 / EC) in collaboration with the disposal company / producer / authority Official.

SODIUM NITRITE

Contact the manufacturer for recycling. Check for recycling. Contact the waste center for recycling

SECTION 14. Transport information

14.1. UN number

ADR / RID, IMDG, 1950
IATA:

14.2. UN proper shipping name

ADR / RID: AEROSOLS
IMDG: AEROSOLS
IATA: AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es)

ADR / RID: Class: 2 Label: 2.1

IMDG: Class: 2 Label: 2.1

IATA: Class: 2 Label: 2.1



SANITIZER FOR HELMETS

14.4. Packing group

ADR / RID, IMDG, -
IATA:

14.5. Environmental hazards

ADR / RID: NO
IMDG: NO
IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: --	Limited Quantities: 1 L	Tunnel restriction code: (D)
	Special Provision: -		
IMDG:	EMS: F-D, S-U	Limited Quantities: 1 L	
IATA:	Cargo:	Maximum quantity: 150 Kg	Packaging instructions: 203
	Pass.:	Maximum quantity: 75 Kg	Packaging instructions: 203
	Special Instructions:	A145, A167, A802	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: P3a

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product
Point 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

SANITIZER FOR HELMETS

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Gas 1A	Flammable gas, category 1A
Aerosol 1	Aerosol, category 1
Aerosol 3	Aerosol, category 3
Ox. Sol. 2	Oxidising solid, category 2
Press. Gas (Liq.)	Liquefied gas
Press. Gas	Pressurised gas
Acute Tox. 1	Acute toxicity, category 1
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: may burst if heated.
H272	May intensify fire; oxidiser.
H280	Contains gas under pressure; may burst if heated.
H330	Fatal if inhaled.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.

SANITIZER FOR HELMETS

H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H400	Very toxic to aquatic life.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and

SANITIZER FOR HELMETS

thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 04 / 08 / 09 / 10 / 11 / 12 / 13 / 14 / 15 / 16.