Revision nr. 1

Dated 12/02/2020

Printed on 12/02/2020

First compilation

Page n. 1/13

PURE LONG LIFE ANTIFREEZE

Safety Data Sheet According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code:

Product name

411 00 16380-4000 fuchsia 5I 411 00 18080-4680 yellow 5I **PURE LONG LIFE ANTIFREEZE**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Antifreeze for cars**

1.3. Details of the supplier of the safety data sheet

Name Full address District and Country Meccanocar Italia S.r.l. Via San Francesco, 22 56033 Capannoli (PI)

Italy

Tel. +39 0587 609433 Fax +39 0587 607145

e-mail address of the competent person

responsible for the Safety Data Sheet moreno.meini@meccanocar.it

1.4. Emergency telephone number

For urgent inquiries refer to National Poisons Information Service: +44 121 507 4123

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Acute toxicity, category 4 H302 Harmful if swallowed.

Specific target organ toxicity - repeated exposure, category 2 H373 May cause damage to organs through prolonged or repeated

exposure.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

PURE LONG LIFE ANTIFREEZE

Revision nr. 1

Dated 12/02/2020
First compilation

Printed on 12/02/2020

Page n. 2/13





Signal words: Warning

Hazard statements:

H302 Harmful if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

P260 Do not breathe dust / fume / gas / mist / vapours / spray.

P264 Wash hands thoroughly after handling.

P301+P312 IF SWALLOWED: Call a POISON CENTER / doctor / . . . / if you feel unwell.

P314 Get medical advice / attention if you feel unwell.

P501 Dispose of contents / container in accordance with local regulations.

Contains: ETHANEDIOL

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

ETHANEDIOL

CAS 107-21-1 96 ≤ x < 100 Acute Tox. 4 H302, STOT RE 2 H373

EC 203-473-3 INDEX 603-027-00-1

Reg. no. 01-2119456816-28-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person,

Meccanocar Italia S.r.I. Revision nr. 1 Dated 12/02/2020 First compilation Pure Long Life Antifreeze Page n. 3/13

unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Revision nr. 1

Dated 12/02/2020 First compilation

Printed on 12/02/2020

Page n. 4/13

PURE LONG LIFE ANTIFREEZE

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition, published 2018)
ITA	Italia	DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017
NOR	Norge	Fastsatt av Arbeids- og sosialdepartementet 21. august 2018 med hjemmel i lov 17. juni 2005 nr. 62 om arbeidsmiljø, arbeidstid, stillingsvern mv. (arbeidsmiljøloven) § 1-3, § 1-4 og § 4-5
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no
		trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive
		2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV/ ACCILI	ACCIII 2040

TLV-ACGIH ACGIH 2019

Туре	Country	TWA/8h	TWA/8h STEL/15min			Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP	52	20	104	40	SKIN
VLEP	FRA	52	20	104	40	SKIN
WEL	GBR	52	20	104	40	SKIN
VLEP	ITA	52	20	104	40	SKIN
TLV	NOR	52	20			SKIN
VLE	PRT	52	20	104	40	SKIN
OEL	EU	52	20	104	40	SKIN
TLV-ACGIH				10		INHAL
TLV-ACGIH			25		50	

PURE LONG LIFE ANTIFREEZE

Revision nr. 1

Dated 12/02/2020

First compilation

Printed on 12/02/2020

Page n. 5/13

Normal value in fresh water	10	mg/l	
Normal value in marine water	1	mg/l	
Normal value for fresh water sediment	37	mg/kg	
Normal value for marine water sediment	3,7	mg/kg	
Normal value of STP microorganisms	199,5	mg/l	
Normal value for the terrestrial compartment	1,53	mg/kg	

Health - Derived no-ef	fect level - DNEL / [OMEL						
	Effects on				Effects on			
	consumers				workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic
				systemic		systemic		systemic
Inhalation			7 mg/m3				35 mg/m3	
Skin				53 mg/kg				106 mg/kg
				bw/d				bw/d

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

Revision nr. 1

Dated 12/02/2020 First compilation

Printed on 12/02/2020

Page n. 6/13

PURE LONG LIFE ANTIFREEZE

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance liquid

Colour various

Odour characteristic

Odour threshold Not available

рΗ 8 Melting point / freezing point -13 °C Initial boiling point 165 °C Boiling range Not available Flash point > 100 °C Evaporation rate Not available Flammability (solid, gas) Not available Lower inflammability limit Not available Upper inflammability limit Not available Lower explosive limit Not available Not available Upper explosive limit Vapour pressure Not available Vapour density Not available

Relative density 1,1

Solubility soluble in water

Partition coefficient: n-octanol/water Not available

Auto-ignition temperature Not available

Decomposition temperature Not available

Viscosity >30 cSt

Explosive properties Not available

Oxidising properties Not available

9.2. Other information

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

ETHANEDIOL

Revision nr. 1

Dated 12/02/2020

First compilation

Printed on 12/02/2020

Page n. 7/13

PURE LONG LIFE ANTIFREEZE

In the air absorbs moisture. Decomposes at temperatures above 200°C/392°F.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

ETHANEDIOL

Risk of explosion on contact with: perchloric acid.May react dangerously with: chlorosulphuric acid,sodium hydroxide,sulphuric acid,phosphorus pentasulphide,chromium (III) oxide,chromyl chloride,potassium perchlorate,potassium dichromate,sodium peroxide,aluminium.Forms explosive mixtures with: air.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

ETHANEDIOL

Avoid exposure to: sources of heat,naked flames.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

ETHANEDIOL

May develop: hydroxyacetaldehyde,glyoxal,acetaldehyde,methane,carbon monoxide,hydrogen.

SECTION 11. Toxicological information

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

ETHANEDIOL

WORKERS: inhalation; contact with the skin.

POPULATION: inhalation of ambient air; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

ETHANEDIOL

Revision nr. 1

Dated 12/02/2020

Printed on 12/02/2020

First compilation

Page n. 8/13

PURE LONG LIFE ANTIFREEZE

Ingestion initially stimulates the central nervous system; later replaced by a phase of depression. There may be kidney damage, with anuria and uremia. Over-exposure symptoms are: vomiting, drowsiness, difficulty in breathing, convulsions. The lethal dose for humans is approx. 1.4 ml/kg.

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture: Not classified (no significant component) LD50 (Oral) of the mixture: 505,05 mg/kg

LD50 (Dermal) of the mixture:

Not classified (no significant component)

ETHANEDIOL

LD50 (Oral) > 2000 mg/kg Rat

LD50 (Dermal) 9530 mg/kg Rabbit

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

ETHANEDIOL

Method: OECD 471 in vitro test

Reliability: 1

Species: S. typhimurium

Results: Negative with and without metabolic activation

Method: Assessing the possible effects of ethylene glycol for reproduction and dominant lethal mutagenesis.-test in vivo

Reliability: 2

Species: Rat (Fischer 344; male / female)

Route of exposure: Oral Results: Negative

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Revision nr. 1

Dated 12/02/2020

First compilation

Printed on 12/02/2020
Page n. 9/13

PURE LONG LIFE ANTIFREEZE

ETHANEDIOL

Available studies have shown no carcinogenic potential. In a carcinogenicity study lasting two years, carried out by the US National Toxicology Program (NTP), in which ethylene glycol was administered in the feed, "no evidence of carcinogenic activity" in male and female B6C3F1 mice was observed (NTP, 1993).

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

ETHANEDIOL

Based on available data and through expert judgment, the substance is classified in the target organ toxicity class for single exposure.

Target organ ETHANEDIOL

Rene

Route of exposure ETHANEDIOL

Orale

STOT - REPEATED EXPOSURE

May cause damage to organs

ETHANEDIOL

Method: OECD 410 Reliability: 1

Species: Dog (Beagle; male / female)

Route of exposure: Dermal

Results: NOAEL> 2 200 - <4 400 mg / kg bw / day

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

12.1. Toxicity

Information not available

12.2. Persistence and degradability

ETHANEDIOL

Revision nr. 1

Dated 12/02/2020

Printed on 12/02/2020

First compilation

Page n. 10/13

PURE LONG LIFE ANTIFREEZE

ETHANEDIOL

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

12.3. Bioaccumulative potential

ETHANEDIOL

Partition coefficient: n-octanol/water -1,36

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

1	4.	1.	UN	num	ber

Not applicable

14.2. UN proper shipping name

Not applicable

Meccanocar Italia S.r.l.	Revision nr. 1
	Dated 12/02/2020
	First compilation
PURE LONG LIFE ANTIFREEZE	Printed on 12/02/2020
	Page n. 11/13
14.3. Transport hazard class(es)	
Not applicable	
14.4. Packing group	
Not applicable	
14.5. Environmental hazards	
Not applicable	
14.6. Special precautions for user	
Not applicable	
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code	
Information not relevant	
SECTION 15. Regulatory information	
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture	
Seveso Category - Directive 2012/18/EC: None	
Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006	
Product Point 3	
Substances in Candidate List (Art. 59 REACH)	
On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.	
Substances subject to authorisation (Annex XIV REACH)	
None	
Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:	

Revision nr. 1

Dated 12/02/2020
First compilation

Printed on 12/02/2020

Page n. 12/13

PURE LONG LIFE ANTIFREEZE

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 4 Acute toxicity, category 4

STOT RE 2 Specific target organ toxicity - repeated exposure, category 2

H302 Harmful if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation

Revision nr. 1

Dated 12/02/2020

First compilation

Printed on 12/02/2020

Page n. 13/13

PURE LONG LIFE ANTIFREEZE

- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP) 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
- 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. 10th Edition

 Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 04 / 08 / 09 / 10 / 11 / 12 / 14 / 15 / 16.