

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 411 00 19570-6145 lavender
411 00 19580-6150 orange
411 00 19590-6155 pine
Product name: SANITIZING DEODORANT FOR CABIN

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Scented sanitizer for car interiors

1.3. Details of the supplier of the safety data sheet

Name: Meccanocar Italia S.r.l.
Full address: Via San Francesco, 22
District and Country: 56033 Capannoli (PI) Italy
Tel. +39 0587 609433
Fax +39 0587 607145
e-mail address of the competent person responsible for the Safety Data Sheet: moreno.meini@meccanocar.it

1.4. Emergency telephone number

For urgent inquiries refer to: National Poisons Information Service: +44 121 507 4123

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Eye irritation, category 2	H319	Causes serious eye irritation.
Skin irritation, category 2	H315	Causes skin irritation.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

SANITIZING DEODORANT FOR CABIN



Signal words: Warning

Hazard statements:

H319 Causes serious eye irritation.
H315 Causes skin irritation.

Precautionary statements:

P280 Wear protective gloves / eye protection / face protection.
P337+P313 If eye irritation persists: Get medical advice / attention.
P264 Wash hands thoroughly after handling.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
PROPAN-2-OL		
CAS 67-63-0	$4 \leq x < 4,5$	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336
EC 200-661-7		
INDEX 603-117-00-0		
Reg. no. 01-2119457558-25-XXXX		
ETHANEDIOL		
CAS 107-21-1	$4 \leq x < 4,5$	Acute Tox. 4 H302, STOT RE 2 H373
EC 203-473-3		
INDEX 603-027-00-1		
Reg. no. 01-2119456816-28-XXXX		
BENZALKONIUM CHLORIDE		
CAS 63449-41-2	$2 \leq x < 2,5$	Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Corr. 1B H314, Eye Dam. 1 H318, Aquatic Acute 1 H400 M=1
EC 264-151-6		
INDEX 612-140-00-5		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SANITIZING DEODORANT FOR CABIN

SECTION 4. First aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.
Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Vapours may catch fire and an explosion may occur; vapour accumulation is therefore to be avoided by leaving windows and doors open and ensuring good cross ventilation. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition,published 2018)
ITA	Italia	DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017
NOR	Norge	Fastsatt av Arbeids- og sosialdepartementet 21. august 2018 med hjemmel i lov 17. juni 2005 nr. 62 om arbeidsmiljø, arbeidstid, stillingsvern mv. (arbeidsmiljøloven) § 1-3, § 1-4 og § 4-5
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2019

ETHANEDIOL				
Threshold Limit Value				
Type	Country	TWA/8h	STEL/15min	Remarks /

		mg/m3	ppm	mg/m3	ppm	Observations		
VLA	ESP	52	20	104	40	SKIN		
VLEP	FRA	52	20	104	40	SKIN		
WEL	GBR	52	20	104	40	SKIN		
VLEP	ITA	52	20	104	40	SKIN		
TLV	NOR	52	20			SKIN		
VLE	PRT	52	20	104	40	SKIN		
OEL	EU	52	20	104	40	SKIN		
TLV-ACGIH				10	INHAL			
TLV-ACGIH			25	50				
Predicted no-effect concentration - PNEC								
Normal value in fresh water				10	mg/l			
Normal value in marine water				1	mg/l			
Normal value for fresh water sediment				37	mg/kg			
Normal value for marine water sediment				3,7	mg/kg			
Normal value of STP microorganisms				199,5	mg/l			
Normal value for the terrestrial compartment				1,53	mg/kg			
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation			7 mg/m3				35 mg/m3	
Skin				53 mg/kg bw/d				106 mg/kg bw/d
PROPAN-2-OL								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
VLA	ESP	500	200	1000	400			
VLEP	FRA			980	400			
WEL	GBR	999	400	1250	500			
TLV	NOR	245	100					
TLV-ACGIH		492	200	983	400			
Predicted no-effect concentration - PNEC								
Normal value in fresh water				140,9	mg/l			
Normal value in marine water				140,9	mg/l			
Normal value for fresh water sediment				552	mg/kg			
Normal value for marine water sediment				552	mg/kg			
Normal value of STP microorganisms				2251	mg/l			
Normal value for the food chain (secondary poisoning)				160	mg/kg			
Normal value for the terrestrial compartment				28	mg/kg			
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic

SANITIZING DEODORANT FOR CABIN

	systemic	systemic	systemic
Oral	26 mg/kg bw/d		
Inhalation	89 mg/m3		500 mg/m3
Skin	319 mg/kg bw/d		888 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

ALCOHOLS, C8-10, ETHOXYLATES

Suitable are protective gloves with the following specifications. The recommendation is valid for laboratory conditions, specific workplace conditions must be taken into consideration separately.

Suitable materials also with prolonged direct contact (Recommended: protection index 6, corresponding to > 480 minutes of breakthrough time according to EN 374):

natural rubber / natural latex (NR) - coating thickness 0.5 mm

SANITIZING DEODORANT FOR CABIN

PROPAN-2-OL

Respiratory protection: personal respiratory protection devices are normally not required. In inadequately ventilated areas, where workplace limits are exceeded, where there are unpleasant odors or where aerosols are present or smoke and fog occur, use a self-contained breathing apparatus or self-contained breathing apparatus with a type A filter or an appropriate combined filter, in compliance with EN 141.

Hand protection: the choice of an appropriate glove depends not only on its material but also on other quality characteristics and is different from one manufacturer to another. Observe the permeability and breakthrough time instructions provided by the glove supplier. Also take into consideration the specific local conditions in which the product is used, such as the danger of cuts, abrasions and contact times., Keep in mind that in daily use the durability of a chemical resistant protective glove can be considerably less than breakthrough time measured according to EN 374.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid
Colour	various
Odour	typical
Odour threshold	Not available
pH	3,8
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	> 60 °C
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	0,997
Solubility	soluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

SANITIZING DEODORANT FOR CABIN

There are no particular risks of reaction with other substances in normal conditions of use.

ETHANEDIOL

In the air absorbs moisture. Decomposes at temperatures above 200°C/392°F.

BENZALKONIUM CHLORIDE

Corrodes: carbon steel, copper, aluminium, copper alloys, aluminium alloys.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

ETHANEDIOL

Risk of explosion on contact with: perchloric acid. May react dangerously with: chlorosulphuric acid, sodium hydroxide, sulphuric acid, phosphorus pentasulphide, chromium (III) oxide, chromyl chloride, potassium perchlorate, potassium dichromate, sodium peroxide, aluminium. Forms explosive mixtures with: air.

PROPAN-2-OL

Vapors can form an explosive mixture with air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

ETHANEDIOL

Avoid exposure to: sources of heat, naked flames.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHANEDIOL

May develop: hydroxyacetaldehyde, glyoxal, acetaldehyde, methane, carbon monoxide, hydrogen.

SECTION 11. Toxicological information

SANITIZING DEODORANT FOR CABIN

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.
It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effectsMetabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

ETHANEDIOL

WORKERS: inhalation; contact with the skin.

POPULATION: inhalation of ambient air; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

ETHANEDIOL

Ingestion initially stimulates the central nervous system; later replaced by a phase of depression. There may be kidney damage, with anuria and uremia. Over-exposure symptoms are: vomiting, drowsiness, difficulty in breathing, convulsions. The lethal dose for humans is approx. 1.4 ml/kg.

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

Not classified (no significant component)

LD50 (Oral) of the mixture:

>2000 mg/kg

LD50 (Dermal) of the mixture:

>2000 mg/kg

PROPAN-2-OL

LD50 (Oral) 4710 mg/kg Rat

LD50 (Dermal) 12800 mg/kg Rat

LC50 (Inhalation) 72,6 mg/l/4h Rat

ETHANEDIOL

LD50 (Oral) > 2000 mg/kg Rat

LD50 (Dermal) 9530 mg/kg Rabbit

SANITIZING DEODORANT FOR CABIN

PROPAN-2-OL

Method: Equivalent or similar to OECD 401

Reliability: 2

Species: Rat (Sherman)

Route of exposure: Oral

Results: LD50: 5.84 other: g / kg body weight

Bibliographic reference: Smyth HF & Carpenter CP, FURTHER EXPERIENCE WITH THE RANGE FINDING TEST IN THE INDUSTRIAL TOXICOLOGY LABORATORY (1948)

Method: Equivalent or similar to OECD 403

Reliability: 1

Species: Rat (Fischer 344; male / female)

Route of exposure: Inhalation (vapor)

Results: LC50: ca. 5,000 ppm

Method: Equivalent or similar to OECD 402

Reliability: 2

Species: Rabbit

Route of exposure: Dermal

Results: LD50: 16.4 mL / kg bw

Bibliographic reference: Smyth HF & Carpenter CP, FURTHER EXPERIENCE WITH THE RANGE FINDING TEST IN THE INDUSTRIAL TOXICOLOGY LABORATORY (1948)

SKIN CORROSION / IRRITATION

Causes skin irritation

PROPAN-2-OL

Method: Not indicated

Reliability: 2

Species: Rabbit

Route of exposure: Dermal

Results: Not classified

Bibliographic reference: Nixon G, Tyson C & Wertz W, Interspecies Comparisons of Skin Irritancy (1975)

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

PROPAN-2-OL

Method: Equivalent or similar to OECD 405

Reliability: 1

Species: Rabbit (New Zealand White)

Route of exposure: Ocular

Results: Category 2

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

PROPAN-2-OL

Method: OECD 406

Reliability: 1

Species: guinea pig (Hartley; male / female)

Route of exposure: Dermal

Results: Not sensitizing

GERM CELL MUTAGENICITY

SANITIZING DEODORANT FOR CABIN

Does not meet the classification criteria for this hazard class

ETHANEDIOL

Method: OECD 471 in vitro test

Reliability: 1

Species: S. typhimurium

Results: Negative with and without metabolic activation

Method: Assessing the possible effects of ethylene glycol for reproduction and dominant lethal mutagenesis.-test in vivo

Reliability: 2

Species: Rat (Fischer 344; male / female)

Route of exposure: Oral

Results: Negative

PROPAN-2-OL

Method: Equivalent or similar to OECD 476 in vitro test

Reliability: 1

Species: Chinese hamster

Results: Negative with or without metabolic activation

Bibliographic reference:

Method: Equivalent or similar to OECD 474 in vivo test

Reliability: 2

Species: Mouse (ICR; male / female)

Route of exposure: Oral

Results: Negative

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

ETHANEDIOL

Available studies have shown no carcinogenic potential. In a carcinogenicity study lasting two years, carried out by the US National Toxicology Program (NTP), in which ethylene glycol was administered in the feed, "no evidence of carcinogenic activity" in male and female B6C3F1 mice was observed (NTP, 1993).

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

PROPAN-2-OL

Method: Equivalent or similar to OECD 416

Reliability: 1

Species: Rat (Sprague-Dawley; male / female)

Route of exposure: Oral

Results: NOAEL 500

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

ETHANEDIOL

Based on available data and through expert judgment, the substance is classified in the target organ toxicity class for single exposure.

SANITIZING DEODORANT FOR CABIN

PROPAN-2-OL

Based on the available data, the substance may cause damage to organs through single exposure and is therefore classified in this hazard class.

Target organ
ETHANEDIOL

Kidney

Route of exposure
ethanediol

Oral

PROPAN-2-OL

inhalation

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ethanediol

Method: OECD 410

Reliability: 1

Species: Dog (Beagle; male / female)

Route of exposure: Dermal

Results: NOAEL > 2 200 - < 4 400 mg / kg bw / day

PROPAN-2-OL

Based on the available data and through expert judgment, the substance is not classified in the target organ hazard class for prolonged or repeated exposure.

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

12.1. Toxicity

ALCOHOLS, C8-10, ETHOXYLATES

EC50 - for Algae / Aquatic Plants

3,4 mg/l/72h

12.2. Persistence and degradability

ALCOHOLS, C8-10, ETHOXYLATES

Quickly biodegradable, 80-90% in 28 days.

ETHANEDIOL

SANITIZING DEODORANT FOR CABIN

PROPAN-2-OL
Quickly degradable in water.

PROPAN-2-OL
Rapidly degradable

BENZALKONIUM CHLORIDE
NOT rapidly degradable

ETHANEDIOL
Solubility in water 1000 - 10000 mg/l
Rapidly degradable

12.3. Bioaccumulative potential

PROPAN-2-OL
Partition coefficient: n-octanol/water 0,05

ETHANEDIOL
Partition coefficient: n-octanol/water -1,36

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

PROPAN-2-OL
After pre-treatment and compliance with the regulations for hazardous waste, they must be taken to a permitted hazardous waste landfill or a hazardous waste incinerator.

SECTION 14. Transport information

SANITIZING DEODORANT FOR CABIN

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: None

SANITIZING DEODORANT FOR CABIN

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006Product

Point 3 - 40

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Acute Tox. 4	Acute toxicity, category 4
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Skin Corr. 1B	Skin corrosion, category 1B
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H373	May cause damage to organs through prolonged or repeated exposure.

SANITIZING DEODORANT FOR CABIN

H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Meccanocar Italia S.r.l.	Revision nr. 2 Dated 14/02/2020
SANITIZING DEODORANT FOR CABIN	Printed on 14/02/2020 Page n. 17/17 Replaced revision:1 (Dated: 23/01/2019)

Note for users:
The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.
This document must not be regarded as a guarantee on any specific product property.
The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.
Provide appointed staff with adequate training on how to use chemical products.
Product`s classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.
The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:
The following sections were modified:
02 / 03 / 08 / 09 / 10 / 11 / 12 / 13 / 15 / 16.