Revision nr. 1

Dated 14/06/2021

First compilation

Printed on 14/06/2021 Page n. 1/13

SEALANT FOR FRAMES AND BUILDING

Safety Data Sheet According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

411 00 21150-6423-White Code: 411 00 21160-6424-Grey

Product name SEALANT FOR FRAMES AND BUILDING

1.2. Relevant identified uses of the substance or mixture and uses advised against

Methoxy-silane based adhesive sealant for general industrial applications Intended use

1.3. Details of the supplier of the safety data sheet

Name Meccanocar Italia S.r.l. Full address Via San Francesco, 22 District and Country 56033 Capannoli (PI)

Italy

Tel. +39 0587 609433 Fax +39 0587 607145

e-mail address of the competent person

responsible for the Safety Data Sheet moreno.meini@meccanocar.it

Product distribution by:

1.4. Emergency telephone number

For urgent inquiries refer to National Poisons Information Service: +44 121 507 4123

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2015/830. Hazard classification and indication:

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:

Signal words:

Hazard statements:

SEALANT FOR FRAMES AND BUILDING

Revision nr. 1

Dated 14/06/2021

First compilation
Printed on 14/06/2021

Page n. 2/13

EUH210 Safety data sheet available on request.

EUH208 Contains:, N-[3-(TRIMETHOXYSILYL)PROPYL]ETHYLENEDIAMINE

May produce an allergic reaction.

Precautionary statements:

--

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. % Classification 1272/2008 (CLP)

MASSA DI REAZIONE DI N,N'-ETANO-1,2-DIILBIS(ESANAMMIDE) E 12-IDROSSIL-N-[2-[(1-OSSIESIL)AMMINO]ETIL]OTTADEC ANAMMIDE E N,N'-ETANO-1,2 -DIILBIS(12-IDROSSIOTTADECANO AMMIDE)

CAS - $2,5 \le x < 3$ Aquatic Chronic 4 H413

EC 432-430-3 INDEX 616-200-00-1

Reg. no. 01-0000017860-69-XXXX

TRIMETOSSIVINILSILANO

CAS 2768-02-7 1,5 \leq x < 2 Flam. Liq. 3 H226, Acute Tox. 4 H332

EC 220-449-8 INDEX -

Reg. no. 01-2119513215-52-XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Revision nr. 1

Dated 14/06/2021

First compilation

Printed on 14/06/2021
Page n. 3/13

SEALANT FOR FRAMES AND BUILDING

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

Meccanocar Italia S.r.I. Revision nr. 1 Dated 14/06/2021 First compilation Printed on 14/06/2021 Page n. 4/13

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

MASSA DI REAZIONE DI N,N'-ETANO-1,2-DIILBIS(ESANAMMIDE) E 12-IDROSSIL-N-[2-[(1-OSSIESIL)AMMINO]ETIL]OTTADECANAMMIDE E N,N'-ETANO-1,2-DIILBIS(12-IDROSSIOTTADECANO AMMIDE)

Predicted no-effect concentration - PNEC			
Normal value in fresh water	0,009	mg/l	
Normal value in marine water	0,001	mg/l	
Normal value for fresh water sediment	384	mg/kg	
Normal value for marine water sediment	38,4	mg/kg	
Normal value of STP microorganisms	100	mg/l	
Normal value for the food chain (secondary poisoning)	222,2	mg/kg	
Normal value for the terrestrial compartment	52,1	mg/kg	

Health - Derived no-ef	fect level - DNEL / [OMEL						
	Effects on				Effects on			
	consumers				workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic
				systemic		systemic		systemic
Oral				5 mg/kg bw/d				
Inhalation								35,24 mg/m3
Skin								10 ma/ka

bw/d

TRIMETOSSIVINILSILANO

Health - Derived no-ef	fect level - DNEL / [OMEL						
	Effects on				Effects on			
	consumers				workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,3 mg/kg bw/d				
Inhalation				18,9 mg/m3				27,6 mg/m3
Skin				7,8 mg/kg bw/d				3,9 mg/kg bw/d

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

SEALANT FOR FRAMES AND BUILDING

Revision nr. 1

Dated 14/06/2021
First compilation

Printed on 14/06/2021

Page n. 5/13

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance paste Colour various Odour characteristic Odour threshold Not available Not available Ηα Melting point / freezing point Not available Initial boiling point Not available Boiling range Not available Flash point Not available Evaporation rate Not available Flammability (solid, gas) Not available Lower inflammability limit Not available Upper inflammability limit Not available Lower explosive limit Not available

Revision nr. 1

Dated 14/06/2021 First compilation

Printed on 14/06/2021
Page n. 6/13

SEALANT FOR FRAMES AND BUILDING

Not available

Upper explosive limit
Vapour pressure
Not available
Vapour density
Not available
Relative density
1,49

Solubility insoluble in water

Partition coefficient: n-octanol/water Not available

Auto-ignition temperature Not available

Decomposition temperature Not available

Viscosity 100000-150000 cps

Explosive properties Not available

9.2. Other information

Information not available

Oxidising properties

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

TRIMETOSSIVINILSILANO

Evitare temperature >150°C

10.5. Incompatible materials

TRIMETOSSIVINILSILANO

Alogeni (cloro) in presenza di luce solare o ultravioletti leggero. Perossidi

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

TRIMETOSSIVINILSILANO

Revision nr. 1

Dated 14/06/2021

Printed on 14/06/2021

First compilation

Page n. 7/13

SEALANT FOR FRAMES AND BUILDING

Ossidi di carbonio, ossidi di silicio

SECTION 11. Toxicological information

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

> 20 mg/l

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

Not classified (no significant component)

MASSA DI REAZIONE DI N,N'-ETANO-1,2-DIILBIS(ESANAMMIDE) E 12-IDROSSIL-N-[2-[(1-OSSIESIL)AMMINO]ETIL]OTTADECANAMMIDE E N,N'-ETANO-1,2-DIILBIS(12-IDROSSIOTTADECANO AMMIDE)

LD50 (Oral) > 2000 mg/kg Rat (male/female)

LD50 (Dermal) > 2000 mg/kg Rat (male/female)

TRIMETOSSIVINILSILANO

Metodo: Equivalente o similare a OECD 401

Affidabilità: 2

Specie: Ratto (Hilltop Wistar albino; maschio/femmina)

Via d'esposizione: Orale

Risultati: LD50=7,34-7,46 mL/kg bw

Metodo: Equivalente o similare a OECD 403

Affidabilità: 2

Specie: Ratto (Fischer 344; maschio/femmina)

Via d'esposizione: Inalazione (vapori)

Risultati: LC50=2773 ppm

Metodo: Equivalente o similare a OECD 402

Revision nr. 1

Dated 14/06/2021

First compilation
Printed on 14/06/2021

Page n. 8/13

SEALANT FOR FRAMES AND BUILDING

Affidabilità: 2

Specie: Coniglio (New Zealand White; maschio/femmina)

Via d'esposizione: Cutanea Risultati: LD50=3,36-4 mL/kg bw

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

TRIMETOSSIVINILSILANO

Metodo: Manuale della FDA Valutazione della sicurezza dei prodotti chimici negli alimenti, nelle droghe e nei cosmetici

Affidabilità: 2

Specie: Coniglio (New Zealand White)

Via d'esposizione: Cutanea Risultati: Non classificato

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

TRIMETOSSIVINILSILANO

Method: OECD 405

Reliability: 1

Species: Rabbit (New Zealand White)

Route of exposure: Ocular Results: Not classified

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

TRIMETOSSIVINILSILANO

Metodo: OECD 476-test in vitro

Affidabilità: 1

Specie: Criceto cinese

Risultati: Negativo con e senza attivazione metabolica

Metodo: OECD 489-test in vivo

Affidabilità: 1

Specie: Ratto (Sprague-Dawley; maschio)

Via d'esposizione: Inalazione

Risultati: Negativo

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

Adverse effects on sexual function and fertility

Revision nr. 1

Dated 14/06/2021 First compilation

Printed on 14/06/2021

Page n. 9/13

SEALANT FOR FRAMES AND BUILDING

TRIMETOSSIVINILSILANO

Metodo: Test di screening della tossicità per la riproduzione ripetuta combinata dell'OECD e la tossicità riproduttiva / dello sviluppo

Affidabilità: 1

Specie: Ratto (Sprague-Dawley; maschio/femmina)

Via d'esposizione: Orale

Risultati: Negativo, NOAEL (fertilità)=1000 mg/kg bw/day

Adverse effects on development of the offspring

TRIMETOSSIVINILSILANO

Metodo: EPA OTS 798.4350 Affidabilità: 1

Specie: Ratto (CD(R))

Via d'esposizione: Inalazione

Risultati: Positivo, NOAEL (sviluppo)=25 ppm

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

TRIMETOSSIVINILSILANO

Based on available data and through expert judgment, the substance is not classified in the target organ toxicity class for single exposure.

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

TRIMETOSSIVINILSILANO

Metodo: OECD 422 Affidabilità: 1

Specie: Ratto (Sprague-Dawley; maschio/femmina)

Via d'esposizione: Orale

Risultati: NOAEL= 62,5 mg/kg bw/day

Metodo: Non indicato

Affidabilità: 1

Specie: Ratto (Fischer 344; maschio/femmina)

Via d'esposizione: Inalazione (vapori)

Risultati: NOAEC=100 ppm

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

12.1. Toxicity

TRIMETOSSIVINILSILANO

 LC50 - for Fish
 137 mg/l/96h

 EC50 - for Crustacea
 121 mg/l/48h

 EC10 for Crustacea
 20 mg/l/28d

Revision nr. 1

Dated 14/06/2021

First compilation Printed on 14/06/2021

Page n. 10/13

SEALANT FOR FRAMES AND BUILDING

Chronic NOEC for Crustacea

20 mg/l

MASSA DI REAZIONE DI N,N'-ETANO-1,2-DIILBIS(ESANAMMIDE) E 12-IDROSSIL-N-OSSIESIL)AMMINO]ETIL]OTTADECANAMM IDE E N,N'-ETANO-1,2 -DIILBIS(12-IDROSSIOTTADECANO AMMIDE) LC50 - for Fish

> 1000 mg/l/96h

12.2. Persistence and degradability

TRIMETOSSIVINILSILANO Degradabile in acqua, 51% in 28 giorni. 12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

TRIMETOSSIVINILSILANO

Può essere incenerito, se conforme alle normative locali.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Managan Kalla O a I	Revision nr. 1
Meccanocar Italia S.r.l.	Dated 14/06/2021
	First compilation
	Printed on 14/06/2021
SEALANT FOR FRAMES AND BUILDING	
	Page n. 11/13
Not applicable	
14.2. UN proper shipping name	
Not applicable	
14.3. Transport hazard class(es)	
Not applicable	
14.4. Packing group	
Not applicable	
14.5. Environmental hazards	
Not applicable	
14.6. Special precautions for user	
Not applicable	
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code	
Information not relevant	
SECTION 15. Regulatory information	
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture	
Seveso Category - Directive 2012/18/EC: None	
Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006	
Product Point 40	
Substances in Candidate List (Art. 59 REACH)	

Revision nr. 1

Dated 14/06/2021
First compilation
Printed on 14/06/2021

Page n. 12/13

SEALANT FOR FRAMES AND BUILDING

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3 Flammable liquid, category 3
Acute Tox. 4 Acute toxicity, category 4

Aquatic Chronic 4 Hazardous to the aquatic environment, chronic toxicity, category 4

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H413 May cause long lasting harmful effects to aquatic life.

EUH210 Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%

Revision nr. 1

Dated 14/06/2021

First compilation

Printed on 14/06/2021 Page n. 13/13

SEALANT FOR FRAMES AND BUILDING

- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- Regulation (EC) 1907/2006 (REACH) of the European Parliament
 Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP) 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
- 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control: therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.